



Gutter

Offset, Chamfer and Box



PRODUCT DATA SHEET



NOTE: FM APPROVAL AND MIAMI-DADE APPROVAL WILL NOT BE AVAILABLE AT INITIAL LAUNCH. APPLICATIONS PENDING.

STANDARD SIZES (Face / Bottom / Back)

- 5.25" / 5.25" / 6.25"
- 5.75" / 5.75" / 6.75"
- 6.25" / 6.25" / 7.25"
- 6.75" / 6.75" / 7.75"
- 7.25" / 7.25" / 8.25"
- 7.75" / 7.75" / 8.75"
- Flange (Optional)

COLORS

Choose from over 30 colors and finishes that meet your job requirements. Finish Warranty is available depending on color selection. See color chart for color and warranty availability.

EFFICIENT DESIGN

- Extruded aluminum internal gutter hangers are adjustable and placed every 2 ft. O.C. to support larger volumes of water, as well as extreme snow and icing conditions and manufactured to rigid tolerances and furnished per required drainage capacity/size.
- Roof Flange is optional (Tested up to 4").
- Provided in 12'-0" lengths for quicker installation and lower labor costs.
- Pre-punched holes; making for easier installation which accommodates the thermal expansion/contraction of the gutter.
- Fastening holes are slotted to allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.

ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.

INCLUDED COMPONENTS

- Gutter
- Concealed Splice Plates
- Extruded Aluminum Internal Bracket
- All fasteners will arrive to the job site with the product

DESCRIPTION

Unique design, superior roof drainage, and attractive appearance make this gutter stand out from the crowd. Mule-Hide's Gutter is specifically engineered and tested to meet the requirements of the ANSI/SPRI GT-1 Standard for Gutter Systems Used with Low-Slope Roofs. The design incorporates a 1" wide extruded internal gutter hanger for strength and support. It also reduces the torque of the metal with expansion and contraction in temperature changes.

PRODUCT HIGHLIGHTS

- ANSI/SPRI GT-1 tested to comply with 2021 International Building Code
- FM Approved for Wind Uplift Protection
- Miami-Dade County Approved
- Variety of color, sizes, and materials
- Prefabricated miters and accessories to eliminate need for field fabrication
- No external brackets or wind straps required

VERSIONS

- Offset, Chamfer and Box

STANDARD MATERIALS

- 24 ga. Steel
- 22 ga. Steel
- .040" Aluminum
- .050" Aluminum
- .063" Aluminum



Gutter

Offset, Chamfer and Box



PRODUCT DATA SHEET

CUSTOM CAPABILITIES

Radius is available to meet the unique needs of each project

TESTING

- ANSI/SPRI GT-1 tested to comply with International Building Code
- Factory Mutual approved for wind uplift protection.
- Miami-Dade Approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made