



LOW-VOC UN-TACK

DESCRIPTION

Rev. Sept 2020

Low-VOC Un-Tack is designed to clean spray guns and hoses used to apply AeroWeb. Low -VOC Un-Tack can also be used to remove adhesives and primers from a variety of surfaces including single-ply membranes, accessories, metal, plastic, rubber, and glass.

TYPICAL PHYSICAL PROPERTIES

Physical Property*	Value
Color	Clear
Consistency	Aerosol Spray
VOC Content	33 g/l
Odor	Slight Solvent
Application Temp	25°F to 100°F

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

PACKAGING

#8 Aerosol Cylinder

APPLICATION INSTRUCTIONS

To Clear Clogged Spray Gun and Hose

- Lock spray gun trigger.
- Attach gun and hose to cylinder.
- Open valve.
- Allow line to charge.
- Let system sit.
- Aim gun away from people, unlock trigger, and spray until clean.
- Repeat until system is clear.

To Clean Up Excess Adhesive

- Spray directly on adhesive to be removed and wipe with cloth.
- Can also spray on cloth and wipe.
- Wear rubber gloves and goggles when cleaning.

Application instructions are basic guidelines only. Please read and understand the complete Mule-Hide specifications prior to use.

PRECAUTIONS

- Flammable liquid propellant and vapor.
- Keep away from open flame.
- Use with adequate ventilation.
- Avoid inhalation of spray mist and vapors. Harmful or fatal if swallowed. May cause eye irritation.
- Keep out of reach of children.
- Use of goggles and gloves recommended.
- Cylinders are not refillable and when empty are harmless and disposable.
- Dispose of according to local codes and laws.
- Keep cans and cylinders below 100°F.

Product Data Sheet

Low-VOC UN-TACK

SHELF LIFE

One-year shelf life from date of manufacture with proper storage.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.