



# One Fascia

Fully Adhered or Mechanically Attached Single-Ply Version



## PRODUCT DATA SHEET

### DESCRIPTION

One Fascia offers quick-to-ship convenience and economical pricing to simplify projects and maximize profits. One Fascia for single-ply roofs protects against high wind events, saving the building from costly damage. The design eliminates the stripping in typical of other products, making One Fascia fast and easy to install.

### PRODUCT HIGHLIGHTS

- ANSI/SPRI/FM 4435/ES-1 Tested
- Variety of colors, sizes and materials
- Easy install = decreased labor costs
- No strip-in or heat welding required

### STANDARD COVER MATERIALS

- 24 ga. Steel
- 22 ga. Steel
- .040" Aluminum
- .050" Aluminum
- .063" Aluminum

### SIZES

- 4"
- 5"
- 6.5"
- 8"

### COLORS

Choose from over 30 colors and finishes that meet your job requirements. Finish Warranty is available depending on color selection. See color chart for color and warranty availability.

### EFFICIENT DESIGN

- Provided in 12'-0" lengths with pre-punched holes for quicker installation and lower labor cost.
- Slotted fastening holes allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.
- Snap-on cover with no exposed fasteners, eliminates any striping or heat welding.

### ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.

**NOTE: FM APPROVAL AND MIAMI-DADE APPROVAL WILL NOT BE AVAILABLE AT INITIAL LAUNCH. APPLICATIONS PENDING.**

### INCLUDED COMPONENTS

- Fascia Cover
- 20 ga. Steel Cleat
- Stainless Steel Springs
- Lap joint or concealed splice plate depending on cover material
- All fasteners will arrive to the job site with the product

### CUSTOM CAPABILITIES

- Radius is available to meet the unique needs of each project

### TESTING

- Testing per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code

### ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

### DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made