



RHINOBOND CARDBOARD DISC

PRODUCT DESCRIPTION

May 2020

RhinoBond Cardboard Disc is used in combination with Induction Weld Plates when installing TPO or PVC membranes directly over EPS insulation. When placed between the plates and the insulation, the RhinoBond Cardboard Disc prevents the insulation from melting during the induction welding process.

FEATURES / BENEFITS

- Compatible with both PVC and TPO
- Pre-punched center hole for easy application
- Fast and easy to install

PACKAGING

Disc's are 4" in Diameter and packaged with 250 pieces per carton and approximate weight is 4" per box.

INSTALLATION INSTRUCTIONS

1. Position the disc between the top layer of insulation and the induction welding plate prior to securement. The hole in the center of the cardboard disc should line up with the center of the plate.
2. Install fastener and induction welding plate per Mule-Hide's specifications and details.
3. Care must be taken not to overdrive fasteners and fracture insulation.

LEED INFORMATION

LEED® Information	
Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Location	Various Locations (AL, TX, AR)

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.