



Product Data Sheet

SEAL-FAST REPAIR HERO

Rev: Sept 2024

PRODUCT DESCRIPTION

Seal-Fast Repair Hero is a superior quality, paintable, high solids adhesive/sealant that forms a tough flexible seal between similar and dissimilar materials such as asphalt, modified bitumen, metal, Kynar®, concrete, TPO, PVC, Elvaloy®/PVC, Hypalon® (CSPE), PIB and EPDM roofs. Extremely strong and elastic with high elongation and tensile strength to ensure performance under conditions that cause asphalt-based cements to fail.



TYPICAL PHYSICAL PROPERTIES

Physical Property	Value*
Viscosity	500,000 cps
Solids by Weight	Approx 75%
Lap Shear	Approx 150 psi
Elongation	Approx 500%
Tensile Strength	1700 psi
Hardness (Shore A)	25-35

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

PACKAGING

1 and 3 gallon containers

COLORS

White, Black, Gray

INSTALLATION INSTRUCTIONS

- Surface must be clean and sound.
- Apply with a roofer's trowel @ 1/8" thickness.
- Taper edges of the repair.
- Polyester fabric may be embedded for added strength.
- Over application on EPDM roofs may cause swelling of the EPDM membrane.

COVERAGE RATES

- Approximately 8 gallons per 100 sq. ft. for a 1/8" (3 mm) coat applied to both surfaces. (All values are approximate and may vary with ambient temperature and job conditions)

CLEAN UP

Uncured sealant can be removed from work surfaces or tools with a solvent, such as naphtha. Use proper precautions when handling solvents. Cured sealant can be removed by cutting with a sharp-edged tool. Thin films of cured sealant can be removed by abrading.

STORAGE & HANDLING

Shelf Life: 24 months with proper storage (unopened containers at temperatures not exceeding 80°F).

SEAL-FAST REPAIR HERO

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

PRECAUTIONS

DANGER: FLAMMABLE LIQUID AND VAPOR

Contains xylene. Keep away from heat, sparks and open flames. Avoid prolonged breathing of vapors and repeated contact with skin. Use with adequate ventilation. Do not take internally. If accidentally swallowed, do not induce vomiting. Call a physician at once. See MSDS for additional Information.

Keep out of reach of children.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.