

#211 Plastic Cement

Asphalt Protective Coating



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time Tested • Weather Tested

Product Description

Mule-Hide #211 Plastic Cement is a general-purpose, cold-applied cement that is ideal for use in sealing and repairing many types of asphalt-based roof membranes.

- Can be used to repair conventional built-up roofs, asphalt shingles, metal, and masonry surfaces.
- Can be used to seal leaks and openings around flashings, such as chimneys, vents, skylights, metal joints, gutters, and similar components of built-up flashings.

Features & Benefits

- An interlocking fiber matrix ensures strong, uniform adhesion to asphalt-based roofing systems, masonry, steel, cured concrete, shingles and tile.
- Will not separate.
- Heavy, trowel-grade consistency makes it well-suited to flashing details and a variety of waterproofing repairs, such as moving joints and roof penetrations.
- Exceptional durability and performance over a wide range of challenging temperatures and weather conditions. Will not mud crack and will remain highly resilient and durable through all seasons.
- Excellent sag resistance when used on vertical surfaces, even at high temperatures.
- Does not damage conventional asphalt-based roofing membranes.
- Easy to use. Ready to apply right out of the container. Smooth texture for hassle-free application using a notched trowel, wide-edged putty knife, or gloved hand.
- Made of 100% recycled cellulose fibers.



Packaging: 2.8 Gallon Pail,
4.7 Gallon Pail

Application Methods:



Code Approvals/Compliance:



D4586 Type I, D3409

#211 Plastic Cement

Asphalt Protective Coating

Used as a component within these systems:

Mod Bit

M&R

Physical Property Information

Property	Value
Maximum VOC	250 G/L
Consistency	Thick Mastic
Weight	8.8 lbs. per gallon
Flash Point (T.C.C)	105°F+
Service Temperature Range	40°F - 90°F
Resistance to Acids, Alkyds	Excellent



Mule-Hide #211 Plastic Cement being applied with a trowel.

Frequently Asked Questions

1. What is the coverage rate for Mule-Hide #211 Plastic Cement?

The coverage rate for Mule-Hide #211 Plastic Cement is approximately 8 gallons per 100 sq. ft. for a 1/8-inch (3 mm) coat applied to both surfaces. (All values are approximate and may vary with ambient temperature and job conditions.)

2. How is Mule-Hide #211 Plastic Cement applied?

Mule-Hide #211 Plastic Cement can be applied using a trowel, a wide-edged putty knife, or a gloved hand.

3. What is the shelf life of Mule-Hide #211 Plastic Cement?

With proper storage, the shelf life of Mule-Hide #211 Plastic Cement is 24 months from the date of manufacture.

4. What temperature should Mule-Hide #211 Plastic Cement be stored at?

Mule-Hide #211 Plastic Cement should be stored at a temperature of at least 45°F but not above 120°F. It should be stored at room temperature for at least 24 hours prior to application.

5. What is the temperature range within which Mule-Hide #211 Plastic Cement can be applied?

Mule-Hide #211 Plastic Cement should only be applied when the ambient temperature is at least 45°F and rising. Cold weather can result in uneven application and improper curing, and it will cause the product to stiffen, making application more difficult. Application is not recommended if the substrate temperature is above 140°F.

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 0 9/21