

# 115 Cleaner

Ready-to-Use General Purpose Cleaner



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

Mule-Hide 115 Cleaner is a ready-to-use roof cleaner which easily cleans dirt, grease, oil and other foreign contamination using little or no agitation. It leaves the surface free of residue. Use it to help clean substrates prior to repairing and/or applying coatings.

## Features & Benefits

- Compatible with Mule-Hide Products silicone and acrylic coating systems.
- Compatible with a wide variety of roof substrates.
- Easily and effectively removes dirt, grease, oil and other grime from the roof surface to ensure proper adhesion of the new primer and finish coats.
- Requires little or no agitation.
- Can be applied with a garden-type airless sprayer.
- Environmentally friendly. It is phosphate-free and contains biodegradable surfactants.
- Safe for crew members and surfaces. It is non-flammable, non-corrosive and non-butyl.

## Frequently Asked Questions

### Does 115 Cleaner need to be diluted?

No. 115 Cleaner is a ready-to-use product.

### What types of coating systems is 115 Cleaner compatible with?

115 Cleaner can be used prior to the application of Mule-Hide Products silicone and acrylic coating systems.

### What types of substrates is 115 Cleaner compatible with?

115 Cleaner can be used to clean a wide variety of roof substrates, including TPO, EPDM and PVC membranes; aged silicone coatings; aged acrylic coatings; aged SEBS coatings; concrete; asphalt built-up roofs; granulated modified bitumen roofs; and metal roofs.



### Packaging:

- 5-Gallon Pail
- 55-Gallon Drum

### Application Method:



Using airless sprayer.

# 115 Cleaner

Ready-to-Use General Purpose Cleaner



## How is 115 Cleaner applied?

The general application steps include the following. For full instructions, see the complete Mule-Hide Products specifications or contact the Mule-Hide Products Technical Department.

- All loose existing coatings, heavy rust, debris and fresh roof cement shall be removed prior to applying 115 Cleaner.
- Apply to surface with a garden type sprayer in sufficient quantity to wet out the surface for a minimum of 15 minutes without drying.
- Apply at a minimum rate of 0.25 to 0.50 gallon per 100 square feet. Do not allow product to dry on roof surface.
- Thoroughly power wash 115 Cleaner from surface until rinse water is clean. A final clean water rinse is recommended. This effectively removes existing oil, dirt, or grease that would adversely affect the bonding of acrylic coatings. Excessively soiled/greasy surfaces and rust or scale may require additional cleaning or scrubbing with a broom or brush.

## Does 115 Cleaner “suds up” when applied to the roof surface?

115 Cleaner is a “controlled” suds formula. It does generate suds, but not to the extent of a cleaner like dishwashing detergent.

Item Number	Description	Gross Weight (lbs)	Units Per Pallet
16MH1155R	5-Gallon Pail	45	36 Pails
16MH1155R	55-Gallon Drum	499	4 Drums



Power washing metal roof.

Used as a component in these systems:



The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 3 8/24