

A-310 Finish

Elastomeric Roof Coating



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

Product Description

A-310 Finish is a 100% Acrylic based high solids, heavy bodied elastomeric roof coating designed for all common roof substrates. Delivering the highest solids content of Mule-Hide Products acrylic coatings, A-310 forms a seamless and flexible layer of protection for your roof. This durable coating is designed to seal and dramatically reduce the surface temperatures. A-310 Finish is formulated with UV reactive chemicals for enhanced film forming characteristics and dirt pickup resistance remaining bright white after weathering.

Features & Benefits

- Engineered for all substrates including spray foam
- Resistant to dirt pickup
- Remains bright white after weathering
- Available in White, Gray or Tan



Packaging:

- 5 Gallon Pail
- 55 Gallon Drum
- 275 Gallon Tote

Application Methods:



Application rates will vary by surface porosity and job conditions.

Codes & Approvals:



For white only

Physical Property Information	
Property	Value
Solids by Weight	69%
Solids by Volume	54%
Flash Point	N/A
VOC	< 50 G/L
Tensile Strength	250 +/- 25 psi
Elongation	185% +/- 50%



The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 0 4/22