

SHUR-GARD

— Roofing Products & Accessories —

Shur-Gard #40 Base Sheet

Shur-Gard #40 Base Sheet

Asphalt Saturated Organic Quality Felt

Product Description

Ideally suited to warm, arid climates, Shur-Gard #40 Base Sheet can be used in built-up roofing (BUR) systems or as the felt layer in steep-slope tile roofing systems. It is constructed of superior-quality felt that is saturated with asphalt, coated on both sides with weathering-grade coating asphalt, and covered on top with mineral surface fines.

Features & Benefits

- Can be mechanically attached to the flat roofing deck or insulation before the application of BUR systems.
- Mineral surface fines prevent sticking in the roll.
- Thinner than fiberglass-based base sheets, Shur-Gard #40 Base Sheets hold in less heat, making them a good choice for use in hot, arid climates. Their use is highly recommended in tile roofing systems in hot climates.
- Meets or exceeds ASTM D2626-04 (Specification for Asphalt Saturated and Coated Organic Felt Base Sheet Used in Roofing).
- Superior pliability and dimensional stability.
- Excellent puncture- and tear-resistance.

Code Approvals/Compliance

- Meets the requirements of ASTM D2626-04.

#40 Base Sheet	Roll Size	Coverage	Weight	Carton	Roll/Pallet	Pallet Size
11MHSGBS43	65' x 39.375"	216 sq. ft.	80 lbs.	2 Sq. Roll	25	42" x 48"



Packaging:

- 2 sq. Roll

Code Approvals/Compliance:



D2626-04



Shur-Gard #40 Base Sheet

Asphalt Saturated Organic Quality Felt

Reference Chart - Shur-Gard #40 Base Sheet

Physical Property	Data (ASTM D2626-04)
Mass of Base Sheet	37.0 lbs./100 sq. ft.
Mass of Asphalt Saturant	7.2 lbs./100 sq. ft.
Mass of Desaturated Felt	5.2 lbs./100 sq. ft.
Mass of Coating and Surfacing (min.)	18.0 lbs./100 sq. ft.
Mass Per Side of Asphalt Coating (Back Coating)	3.5 lbs./100 sq. ft.
Saturation Efficiency (min.) by Weight Breaking Strength at 77°F (min.)	100%
Machine Direction	35 lbf./in.
Cross Direction	20 lbf./in.
Water Vapor Performance	0.3 grains/hr. ftsq. (in. HG) 1/2" Radius

Frequently Asked Questions

1. What types of roof decks can Shur-Gard #40 Base Sheet be attached to?

Shur-Gard #40 Base Sheet can be attached to steel, concrete, and wood roof decks.

2. How is Shur-Gard #40 Base Sheet attached?

Shur-Gard #40 Base Sheet is attached using mechanical fasteners.

3. What warranty coverage is offered for Shur-Gard #40 Base Sheet?

Shur-Gard #40 Base Sheet is backed by Mule-Hide Product Co.'s standard one-year materials-only warranty.

MORE INFO



The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 0 9/21