



JTS 1

Joint & Termination Sealant

Product Description

JTS 1 Joint & Termination Sealant is a moisture-cure urethane sealant made with 100% solids. JTS 1 seals large joints and roof termination bars and adheres to concrete, masonry, EPDM, PVC, TPO (primed), wood, vinyl and most other common building materials. Available in 10-oz plastic tubes, 12 per carton.

Feature/Benefits

- Isocyanate-free for improved stability & moisture tolerance for wet surface application
- No sagging or shrinkage
- Cures quickly
- Submerge product and adhere under water with wet/dry application
- Packaged in a durable plastic tube
- Excellent workability
- Minimal odor
- Contains less than 10 g/L allowable VOC content for areas with VOC transportation restrictions
- Nine color options: White, Black, Bronze, Medium Bronze, Gray, Limestone, Wicker/Tan, Terra Cotta, Clear



Why Contractors value Mule-Hide JTS 1

- Ease of application—Sag-free, shrink-free, workable, wet/dry application
- Competitive price
- Durable plastic tubes outlast paper tubes
- Available nationwide through ABC Supply

FAQ

Is JTS 1 required for a Mule-Hide Warranty?

Not at this time, perhaps in the future.



Joint & Termination Sealant Comparison Chart

	Mule-Hide JTS 1	Geocel 3300	Masterseal NP-1	RM Lucas 9600	Sika 1-A	Vulkem 116
Gap Filling	2"	1/2"	1/2"	2"	1/2"	1/2"
Elongation	400%	881%	800%	400%	550%	200-300%
Cure Time	1 Day	1 Day	Approx. 7 Days	1 Day	4-7 Days	4-7 Days
Tack Free Time	2 Hours	3 Hours	Maximum of 72 Hours	2 Hours	3-6 Hours	30 Hours
Cold Weather Application	Yes but will increase cure time	Yes	Can be applied below freezing temps only if substrates are completely dry, clean and free of moisture. Warm product for 24 hours before using.	Yes but will increase cure time	Condition units at approx. 70° F, remove prior to use.	Warm sealant & bonding surfaces, clean substrates with a solvent.
Paintable	Yes	Yes	Yes	Yes	Yes	Yes
Meets ASTM C 920	Yes	Yes	Yes	Yes	Yes	Yes

The competitive information is assembled using the latest information available in the marketplace via manufacturers published technical data, SDS, PDS and website. Every effort has been made to ensure its accuracy. Cure Time and Tack Free Times may vary pending weather temperature and humidity levels. If you should have any questions, please contact the appropriate manufacturer.