

MSISFILE: Dec-Tec REVISION DATE: 1/1/2014

# **Material Safety Information Sheet**

(According to 29 CFR 1910.1200(5)(v)© this material is an article. No labeling or MSDS reporting is required.)

# SECTION 1: Product and Company Identification

TRADE NAME: Dec-Tec Membrane SYNONYMS: Vinyl Deck Membrane

MANUFACTURER: Sika Sarnafil Corp

ADDRESS: 225 Dan Road, Canton, MA 02021

EMERGENCY NUMBERS: CHEMTRAC Transportation Emergency (24 hr.) (800) 424-9300

MSDS and Product Information (M-F, 8:30am-5:00pm EST) (800) 451-2504

# SECTION 2: Information on Hazardous Ingredients

This material is considered an article according to 29 CFR 1910.1200(5)(v)(c). An article is by definition a manufactured item other than a fluid or particle: (I) which is formed to a specific shape or design during manufacture; (ii) which has end use functions(s) dependent in whole or part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees.

An MSDS is required only for chemicals in products that are hazardous as defined by the OSHA standard 29 CFR 1910.1200. This Material Safety Information Sheet is provided in lieu of a Material Safety Data Sheet.

<u>CHEMICAL COMMON NAME</u> <u>CAS NUMBER</u> <u>PERCENTOSHA-PEL</u> <u>ACGIH-TLV</u>

Antimony Trioxide 1309-64-4 < 2.0% 0.5 mg/m3 0.5 mg/m3

Barium Compounds 2457-01-4 < 1.5% Not Listed Not Listed

## **SECTION 3:** Hazards Identification

None known.

EYES: May irritate eyes during thermal welding.

SKIN: May irritate skin during thermal welding.

INHALATION: None known.

INGESTION:

SYMPTOMS: May cause skin sensitization in some people due to antimony trioxide.

## **SECTION 4:** First Aid Measures

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical

attention.

SKIN: Wash skin with soap and plenty of water.

INHALATION: If exposed to fumes from thermal decomposition (flame), remove to fresh air. If not breathing, give

artificial respiration and seek medical attention immediately. Trained personnel should only administer

oxygen.

INGESTION: If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of a physician.

Never give anything by mouth to an unconscious person.

Page 1 of 4

<u>www.dec-tec.com</u> (800) 268-1078



MSISFILE: Dec-Tec REVISION DATE: 1/1/2014

**SECTION 5:** Fire Fighting Measures

FLASH POINT (F/C) LEL (volume %) **UEL** (volume %

Extinguishing Media: Carbon dioxide, dry chemical, foam or water spray.

Fire Fighting Procedures: Wear a self-contained breathing apparatus.

**Unusual Hazards:** 

Combustion Products: Toxic gases such as carbon dioxide, carbon monoxide, metal oxides and hydrochloric acid

may form if ignited by flame.

SECTION 6: Accidental Release Measures

Use normal cleanup procedure for solid materials.

**SECTION 7:** Handling and Storage

Store material away from heat and flame.

**SECTION 8:** Exposure Controls / Personal Protection

Mechanical ventilation may be necessary if working with the product in enclosed **Engineering Controls:** 

areas at elevated temperatures as experienced during thermal welding.

Personal Protective Equipment:

EYES: Safety glasses. Consult your safety representative.

SKIN: Gloves recommended.

RESPIRATORY: NIOSH approved respirator is recommended if exposure to airborne contaminants

exceeds acceptable limits.

**Exposure Guidelines:** 

**OSHA CHEMICAL** ACHIG TLV **Antimony Trioxide** Pel = 0.5 mg/m3TWA = 0.5 mg/m3

**Barium Compounds** Not Listed Not Listed

PEL = Permissible Exposure Limits TWA = Time Weighted Average (8 hr.) TLV = Threshold Limit Value

STEL = Short Term Exposure Limit (15 min.)

Page 2 of 4



MSISFILE: Dec-Tec REVISION DATE: 1/1/2014

# SECTION 9: Physical and Chemical Properties

APPEARANCE: Solid flexible membrane.

ODOR: None

BOILING POINT (@ 760 mm Hg): N/A

SPECIFIC GRAVITY (air=1): 1.27

LIQUID DENSITY: N/A

SOLUBILITY IN WATER: Insoluble

% VOLATILE VOLUME: N/A

**EVAPORATION RATE (N-Butyl Acetate=1):** N/A

VAPOR PRESSURE (mm Hg): N/A

VAPOR DENSITY (air=1): N/A

# **SECTION 10:** Stability and Reactivity

## **CONDITIONS TO AVOID:**

Prolonged excessive heat, sparks, open flame and smoking.

#### INCOMPATABILITY WITH OTHER MATERIALS:

N/A

#### HAZARDOUS DECOMPOSITION PRODUCTS:

Toxic gases such as carbon dioxide, carbon monoxide, metal oxides and hydrochloric acid may form if ignited by flame.

#### **HAZARDOUS POLYMERIZATION:**

Will NOT undergo hazardous polymerization.

# SECTION 11: Toxicological Information

Toxicological information is not available.

## **SECTION 12:** Ecological Information

Ecological information is not available.

## **SECTION 13:** Disposal Considerations

Dispose in accordance with applicable Federal, State, and Local regulations. Meets the Commonwealth of Massachusetts Department of Environmental Protection TCLP requirements for land fill disposal.

Page 3 of 4

<u>www.dec-tec.com</u> (800) 268-1078



MSISFILE: Dec-Tec REVISION DATE: 1/1/2014

# SECTION 14: Transportation Information

D.O.T. Primary Hazard Label:

D.O.T. Hazard Class:

Not Regulated
D.O.T. Identification Number (UN/NA):

None Required
D.O.T. Packing Group:

Not Regulated

# **SECTION 15:** Disposal Considerations

## **U.S. Federal Regulations**

#### **SAA Title III, Section 302:**

This product is NOT regulated under SARA Title III, Section 302 Extremely Hazardous Substances (40 CFR Part 355).

#### SARA Title III, Section 313:

This product contains toxic chemicals subject to the reporting requirements of SARA title 111, Section 313 (40 CFR 372) of the Emergency Planning and Community Right-To-Know Act of 1986.

## **State Regulations**

#### CALIFORNIA SAFE DRINKING ACT (PROP 65 for Carcinogen and Teratogen):

This product contains chemicals currently on the California List of Known carcinogens and Reproductive Toxins.

<u>CAS #</u> <u>Chemical Name</u> 1309-64-4 <u>Antimony Trioxide</u>

# SECTION 16: Other Information

	<u>HMIS</u>	NFPA
HEALTH:	0	N/A
FLAMMABILITY:	1	1
REACTIVITY:	0	0
PERSONAL PROTECTION:	В	N/A

# Skyline Building Systems, Inc. Disclaimer of Expressed and Implied Warranties

The information in this Material Safety Information Sheet is offered in good faith as accurate at the date of issuance. No warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the safety of this product, or the hazards related to its use. This information and product are furnished on the condition that the person receiving it shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of use thereof. Compliance with all applicable Federal, State, and Local laws and regulations remains the responsibility of the user.

Page 4 of 4

<u>www.dec-tec.com</u> (800) 268-1078