



# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/26/2015 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : MULE-HIDE # 231 FLASHING CEMENT  
Product code : MUL-231  
Formula : 700-TRO-501

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Roofing/Waterproofing

#### 1.3. Details of the supplier of the safety data sheet

MULE-HIDE PRODUCTS CO., INC  
1195 PRINCE HALL DRIVE  
BELOIT, WI 53511 - United States  
T (608)365-3111

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300  
Chemtrec

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification


Flam. Liq. 2 H225  
Muta. 1B H340  
Carc. 1B H350  
STOT RE 1 H372

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS08

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour  
H340 - May cause genetic defects (Dermal, Inhalation)  
H350 - May cause cancer (Inhalation, Dermal)  
H372 - Causes damage to organs (central nervous system, eye, Skin, lung, liver) through prolonged or repeated exposure (Dermal, Inhalation)

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from open flames. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe fume, gas, vapours  
P264 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P280 - Wear protective gloves, protective clothing  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P370+P378 - In case of fire: Use carbon dioxide (CO2), foam, dry extinguishing powder to extinguish

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
asphaltic bitumen, not cut back	(CAS No) 8052-42-4	60 - 80	Not classified
kaolin	(CAS No) 1332-58-7	15 - 30	Not classified
Stoddard solvent	(CAS No) 8052-41-3	20 - 25	Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
attapulgate	(CAS No) 12174-11-7	5 - 10	Carc. 2, H351
cellulose	(CAS No) 9004-34-6	3 - 7	Not classified

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : There are potential chronic health effects to consider.

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.

Symptoms/injuries after skin contact : May cause an allergic skin reaction. May cause moderate irritation.

Symptoms/injuries after eye contact : Eye irritation.

Symptoms/injuries after ingestion : No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapour-air mixture.

Reactivity : Upon combustion: CO and CO2 are formed.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage. Isolate from fire, if possible, without unnecessary risk. No flames, no sparks. Eliminate all sources of ignition. Remove ignition sources.

##### 6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Gloves.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

Emergency procedures : Stop release.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Do not breathe fume, spray, vapours.

Handling temperature : < 110 (≤ 100) °F

Hygiene measures : Do not eat, drink or smoke when using this product. Wash Always wash hands after handling the product, Do not eat, drink or smoke when using this product, Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition.

Storage temperature : < 43 °C

Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: ignition sources.

Prohibitions on mixed storage : No data available.

Storage area : Meet the legal requirements.

Special rules on packaging : Keep only in original container. meet the legal requirements. Store in a closed container. correctly labelled.

Packaging materials : No data available.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

MULE-HIDE # 231 FLASHING CEMENT	
ACGIH	Not applicable
OSHA	Not applicable
asphaltic bitumen, not cut back (8052-42-4)	
OSHA	Not applicable

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>attapulgite (12174-11-7)</b>	
ACGIH	Not applicable
OSHA	Not applicable
<b>cellulose (9004-34-6)</b>	
OSHA	Not applicable
<b>kaolin (1332-58-7)</b>	
OSHA	Not applicable

### 8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Materials for protective clothing	: PICM010.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: BLACK FIBERED MASTIC.
Colour	: Black
Odour	: Petroleum-like odour
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 300 (≤ 450) °F
Flash point	: 106 °F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.293 kPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: 1.02 - 1.12
Density	: 8.5 - 9.3
Percent Solids	: > 75 %
Solubility	: Water: 0 % Acetone: ≈ g/100ml Organic solvent: ≈ 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available

### 9.2. Other information

VOC content	: < 250 (≤ 250) g/l
-------------	---------------------

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified  
(Lack of data)

asphaltic bitumen, not cut back (8052-42-4)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)

cellulose (9004-34-6)	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 6 mg/l/4h (Rat)

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : May cause genetic defects (Dermal, Inhalation).  
Carcinogenicity : May cause cancer (Inhalation, Dermal).

asphaltic bitumen, not cut back (8052-42-4)	
IARC group	3 - Not classifiable

attapulgite (12174-11-7)	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Causes damage to organs (central nervous system, eye, Skin, lung, liver) through prolonged or repeated exposure (Dermal, Inhalation).

Aspiration hazard : Not classified  
Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.  
Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause an allergic skin reaction.  
Symptoms/injuries after skin contact : May cause an allergic skin reaction. May cause moderate irritation.  
Symptoms/injuries after eye contact : Eye irritation.  
Symptoms/injuries after ingestion : No data available.

### SECTION 12: Ecological information

#### 12.1. Toxicity

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>asphaltic bitumen, not cut back (8052-42-4)</b>	
LC50 fish 1	> 1000 mg/l (96 h; Pisces)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)

<b>cellulose (9004-34-6)</b>	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)

### 12.2. Persistence and degradability

<b>MULE-HIDE # 231 FLASHING CEMENT</b>	
Persistence and degradability	Not established.

<b>asphaltic bitumen, not cut back (8052-42-4)</b>	
Persistence and degradability	Not readily biodegradable in water.

<b>attapulgite (12174-11-7)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

<b>cellulose (9004-34-6)</b>	
Persistence and degradability	Biodegradable in water.

<b>kaolin (1332-58-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

<b>MULE-HIDE # 231 FLASHING CEMENT</b>	
BCF fish 1	>
Bioaccumulative potential	Not established.

<b>asphaltic bitumen, not cut back (8052-42-4)</b>	
Log Pow	> 6 (Calculated)
Bioaccumulative potential	Not bioaccumulative.

<b>attapulgite (12174-11-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>cellulose (9004-34-6)</b>	
Bioaccumulative potential	Bioaccumulation: not applicable.

<b>kaolin (1332-58-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

<b>Stoddard solvent (8052-41-3)</b>	
Log Pow	3.16-7.06

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations.
Additional information	: Industrial waste.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

In accordance with DOT	
Transport document description	: Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated, III
UN-No.(DOT)	: Combustible Liquid - DOT 49 CFR 173.150 SUB.PAR.F. Unregulated
Packing group (DOT)	: III - Minor Danger

#### Additional information

Other information : No supplementary information available.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### MULE-HIDE # 231 FLASHING CEMENT

Not listed on the United States SARA Section 313

##### asphaltic bitumen, not cut back (8052-42-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### attapulgite (12174-11-7)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

##### cellulose (9004-34-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### kaolin (1332-58-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Stoddard solvent (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

#### 15.2.2. National regulations

# MULE-HIDE # 231 FLASHING CEMENT

## Safety Data Sheet 10-8530

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

#### MULE-HIDE # 231 FLASHING CEMENT()

U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

#### attapulgit (12174-11-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### asphaltic bitumen, not cut back (8052-42-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### cellulose (9004-34-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### kaolin (1332-58-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### Stoddard solvent (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:

----- Asp. Tox. 1	Aspiration hazard, Category 1
----- Carc. 1B	Carcinogenicity, Category 1B
----- Carc. 2	Carcinogenicity, Category 2
----- Flam. Liq. 2	Flammable liquids, Category 2
----- Muta. 1B	Germ cell mutagenicity, Category 1B
----- STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
----- H225	Highly flammable liquid and vapour
----- H304	May be fatal if swallowed and enters airways
----- H340	May cause genetic defects
----- H350	May cause cancer
----- H351	Suspected of causing cancer
----- H372	Causes damage to organs through prolonged or repeated exposure

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
 Flammability : 2 Moderate Hazard  
 Physical : 0 Minimal Hazard  
 Personal Protection : p

ZGeneric SDS B&W

*All information contained in this MSDS is based on current technical data believed to be accurate and reliable. Additions of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since these conditions are outside our control, we furnish this MSDS without any express or implied warranties.*