

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 06/26/2015 Supersedes: 01/27/2011 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Mule-Hide A-200 Flashing Grade

Product form : Mixture
Product code : EAC-004

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Mule-Hide Products Co., Inc 1195 Prince Hall Drive PO Box 1057 Beloit, WI 53511

T 608-365-3111, 800-786-1492

www.mulehide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Sens. 1 H317 Carc. 1A H350

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction

H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P261 - Avoid breathing vapours

P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear eye protection, face protection, protective clothing, protective gloves

P302+P352 - If on skin: Wash with plenty of soap and water
P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see first aid instructions on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Silica: Crystalline, quartz	(CAS No) 14808-60-7	0.1 - 1
3(2H)-Isothiazolone, 2-octyl-	(CAS No) 26530-20-1	0.01 - 0.1

06/26/2015 Mule-Hide A-200 Flashing Grade Page 1

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the

doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an

unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if breathing is affected. If breathing is difficult, supply oxygen.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at

least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact

lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get

medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison

control center or medical professional. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Chronic symptoms : May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Dry powder. Water spray.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Product will not burn until all water content has evaporated.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the

environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews

properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place

in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

06/26/2015 Mule-Hide A-200 Flashing Grade 2/1

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Provide good ventilation in process area to prevent formation of vapor. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe vapours. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep from freezing. Close container after use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Silica: Crystalline, quartz (14808-60-7)		
ACGIH TWA (mg/m³)	0.025 (respirable fraction)	
OSHA PEL (TWA) (mg/m³)	(30)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction	
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction	

3(2H)-Isothiazolone, 2-octyl- (26530-20-1)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

8.2. **Exposure controls**

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment Gloves. Protective goggles. Protective clothing.







Use gloves chemically resistant to this material when prolonged or repeated contact could Hand protection

> occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate,

PVC or vinyl.

: Wear eye protection, including chemical splash goggles and a face shield when possibility Eye protection

exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure. Respiratory protection

: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or

3/1

other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color White. Odor : Acrylate odor. Odor Threshold : No data available : No data available

Relative evaporation rate (butylacetate=1)

Melting point Same as water Freezing point : No data available Boiling point : 100 °C (212 °F) : > 100 °C (212 °F) Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure : 17 mm Hg At 68 °F Relative vapour density at 20 °C : ≤ 1 (AIR = 1) Relative density : No data available : 1.438 kg/l Density

06/26/2015 Mule-Hide A-200 Flashing Grade

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility : Infinitely dilutable. Log Pow : No data available Log Kow No data available Viscosity, kinematic No data available Viscosity, dynamic : No data available Explosive properties : No data available Oxidising properties No data available Explosive limits No data available

Volatility : 36%

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep from freezing.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2). Nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Silica: Crystalline, quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
ATE CLP (oral)	500.000 mg/kg bodyweight

3(2H)-Isothiazolone, 2-octyl- (26530-20-1)	
LD50 oral rat	550 mg/kg
LD50 dermal rabbit	690 mg/kg

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

Silica: Crystalline, quartz (14808-60-7)

IARC group 1 - Carcinogenic to humans

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified exposure)

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Chronic symptoms : May cause cancer.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

06/26/2015 Mule-Hide A-200 Flashing Grade 4/1

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Mule-Hide A-200 Flashing Grade	
Persistence and degradability	No information available.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities.

No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the

product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Not hazardous for transport

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Mule-Hide A-200 Flashing Grade	
All chemical substances in this product are lis	ted in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Cadmium (pyrophoric) (7440-43-9)	
CERCLA RQ	10 lb
Section 313	Listed on US SARA Section 313
Lead (7439-92-1)	
CERCLA RQ	10 lb
Section 313	Listed on US SARA Section 313
Ammonium hydroxide (1336-21-6)	
CERCLA RQ	1000 lb
Ammonia (7664-41-7)	
Section 302 (EHS) TPQ	500 lb
Section 304 EHS RQ	100 lb
CERCLA RQ	100 lb
Ethylene glycol (107-21-1)	
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 313

15.2. International regulations

No additional information available.

15.3. US State regulations

California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

06/26/2015 Mule-Hide A-200 Flashing Grade 5/1

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

alifornia - ion 65 - mental Toxicity alifornia - ion 65 - mental Toxicity alifornia - ion 65 - mental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Female No No	U.S California - Proposition 65 - Reproductive Toxicity - Male No U.S California - Proposition 65 - Reproductive Toxicity - Male No U.S California - Proposition 65 - Reproductive Toxicity - Male Ves	No significance risk level (NSRL) No significance risk level (NSRL) No significance risk level (NSRL)
ion 65 - mental Toxicity alifornia - ion 65 -	U.S California - Proposition 65 - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male No U.S California - Proposition 65 - Reproductive Toxicity - Male	(NSRL) No significance risk leve
ion 65 - mental Toxicity alifornia - ion 65 -	Proposition 65 - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male No U.S California - Proposition 65 - Reproductive Toxicity - Male	(NSRL) No significance risk level
ion 65 - mental Toxicity alifornia - ion 65 -	Proposition 65 - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male No U.S California - Proposition 65 - Reproductive Toxicity - Male	(NSRL) No significance risk level
ion 65 -	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	
ion 65 -	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	
ion 65 -	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	
	No	Vec	
		103	
	·		
alifornia - ion 65 - mental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes	Yes	
	·	<u> </u>	
alifornia - ion 65 - mental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	No	No	
	•	•	•
alifornia - ion 65 - mental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	No	No	
	ion 65 - mental Toxicity alifornia - ion 65 - mental Toxicity alifornia - ion 65 -	ion 65 - mental Toxicity Proposition 65 - Reproductive Toxicity - Female Yes U.S California - Proposition 65 - Reproductive Toxicity - Proposition 65 - Reproductive Toxicity - Female No U.S California - Reproductive Toxicity - Female No U.S California - Proposition 65 - Reproductive Toxicity - Proposition 65 - Reproductive Toxicity - Female	ion 65 - mental Toxicity Proposition 65 - Reproductive Toxicity - Female Yes Yes Ves U.S California - Proposition 65 - Reproductive Toxicity - Male Ves U.S California - Proposition 65 - Reproductive Toxicity - Reproductive Toxicity - Female No No No U.S California - Proposition 65 - Reproductive Toxicity - Male No No No No No No Allifornia - Proposition 65 - Reproductive Toxicity - Male U.S California - Proposition 65 - Reproductive Toxicity - Proposition 65 - Reproductive Toxicity - Reproductive Toxicity - No Male

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Silica: Crystalline, quartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

Titanium dioxide (13463-67-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Silica, amorphous (7631-86-9)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) List

Zinc oxide (1314-13-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Cadmium (pyrophoric) (7440-43-9)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

06/26/2015 Mule-Hide A-200 Flashing Grade 6

Safety Data Sheet 10-9620

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cadmium (pyrophoric) (7440-43-9)

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

Lead (7439-92-1)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Ammonium hydroxide (1336-21-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

1,2-Propylene glycol (57-55-6)

- U.S. New Jersey Right to Know Hazardous Substance List U.S. Pennsylvania RTK (Right to Know) List

Ammonia (7664-41-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

Ethylene glycol (107-21-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created

: 06/26/2015 Revision date Other information : Author: ANF.


NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

: 3* Health Flammability : 0 Physical : 0 Personal Protection

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/26/2015 Mule-Hide A-200 Flashing Grade 7/1