

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Low VOC Bonding Adhesive 1168

Synonyms

Bonding Adhesive

Chemical Family

Adhesive

Product Use

Low VOC Contact Adhesive

Restrictions on Use

For industrial use only.

Manufacturer Information:

Carlisle SynTec
1285 Ritner Highway
Carlisle, PA 17013
USA
Phone: +1-800-479-6832
Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Supplier Information:

Mule-Hide Products Co., Inc
1195 Prince Hall Dr.
Beloit, WI 53511
USA
Phone: 800-786-1492

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 1 (central nervous system)

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (central nervous system)

Specific Target Organ Toxicity - Repeated Exposure - Category 2 (blood)

GHS Label Elements

Symbol(s)



Signal Word

Danger

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Hazard Statement(s)

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes serious eye irritation
May cause allergic skin reaction
Suspected of causing cancer
Causes damage to organs
May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
May cause damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep container tightly closed
Keep away from heat/sparks/open flame/hot surfaces - No smoking
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Take precautionary measures against static discharge
Use only non-sparking tools
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Do not breathe dust/fume/gas/mist/vapours/spray
Wash thoroughly after handling
Contaminated work clothing must not be allowed out of the workplace
Do not eat, drink or smoke when using this product

Response

In case of fire: Use appropriate media to extinguish
If exposed: Call a POISON CENTER or doctor/physician
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF SWALLOWED: Immediately call a POISON CENTER/doctor
Do NOT induce vomiting
Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed
Keep cool
Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Other Hazards

No additional information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Mixture	Chlorinated polypropylene	0.1-1
Trade Secret	Polyphenol antioxidant	0.1-1
1309-48-4	Magnesium oxide	0.1-1
1314-13-2	Zinc oxide	0.1-1
Trade Secret	Heat reactive phenolic resin	1-5
108-88-3	Toluene	3-7
67-64-1	Acetone	1-5
Mixture	Polychloroprene polymer	10-30
98-56-6	PCBTF	60-100

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Remove contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation or rash occurs, seek medical advice/attention.

Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause allergic skin reaction. Causes damage to central nervous system. May cause drowsiness or dizziness.

Delayed

Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure: central nervous system, blood.

Note to Physicians

Contains toluene.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen

Advice for firefighters

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/bond container and receiving equipment. Take action to prevent static discharges.

Fire Fighting Measures

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment.

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Take precautionary measures against static discharge. Use non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. **KEEP OUT OF REACH OF CHILDREN.**

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep away from heat and ignition sources. Do not cut, puncture, or weld on or near this container. Empty containers may contain product residue.

Incompatible Materials

Acids, bases, strong oxidizing agents

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Magnesium oxide	1309-48-4	
ACGIH:	10 mg/m ³ TWA inhalable fraction	
NIOSH:	750 mg/m ³ IDLH fume	
OSHA (US):	15 mg/m ³ TWA fume, total particulate	
Mexico:	10 mg/m ³ TWA LMPE-PPT as Mg fume	
Zinc oxide	1314-13-2	
ACGIH:	2 mg/m ³ TWA respirable fraction	10 mg/m ³ STEL respirable fraction
NIOSH:	5 mg/m ³ TWA dust and fume	10 mg/m ³ STEL fume
	15 mg/m ³ Ceiling dust	500 mg/m ³ IDLH
OSHA (US):	5 mg/m ³ TWA fume; 15 mg/m ³ TWA total dust; 5 mg/m ³ TWA respirable fraction	
Mexico:	5 mg/m ³ TWA LMPE-PPT fume; 10 mg/m ³ TWA LMPE-PPT dust	
	10 mg/m ³ STEL [LMPE-CT] fume	

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

Toluene	108-88-3	
ACGIH:	20 ppm TWA	
NIOSH:	100 ppm TWA; 375 mg/m ³ TWA	150 ppm STEL; 560 mg/m ³ STEL
	500 ppm IDLH	
Europe:	50 ppm TWA; 192 mg/m ³ TWA	100 ppm STEL; 384 mg/m ³ STEL
	Possibility of significant uptake through the skin	
OSHA (US):	200 ppm TWA	300 ppm Ceiling
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m ³ TWA LMPE-PPT	
	Skin - potential for cutaneous absorption	
Acetone	67-64-1	
ACGIH:	250 ppm TWA	500 ppm STEL
NIOSH:	250 ppm TWA; 590 mg/m ³ TWA	2500 ppm IDLH (10% LEL)
Europe:	500 ppm TWA; 1210 mg/m ³ TWA	
OSHA (US):	1000 ppm TWA; 2400 mg/m ³ TWA	
Mexico:	1000 ppm TWA LMPE-PPT; 2400 mg/m ³ TWA LMPE-PPT	
	1260 ppm STEL [LMPE-CT]; 3000 mg/m ³ STEL [LMPE-CT]	

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment
Eye/face protection

Wear chemical safety goggles with a faceshield to protect against skin and eye contact when appropriate.

Skin Protection

Wear work clothes with long sleeves. Wear protective shoes.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	yellowish liquid	Physical State	liquid
Odor	hydrocarbon	Color	yellowish
Odor Threshold	Not available	pH	Not available
Melting Point	-95 - -33 °C (-139--27 °F)	Boiling Point	56 - 139 °C (133-283 °F)
Freezing point	Not available	Evaporation Rate	1.2
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	465 °C (869 °F)	Flash Point	-17 °C (0 °F)
Lower Explosive Limit	0.9 %	Decomposition	Not available
Upper Explosive Limit	12.8 %	Vapor Pressure	12.5 mmHg
Vapor Density (air=1)	5.8	Specific Gravity (water=1)	Not available
Water Solubility	Negligible	Partition coefficient: n-octanol/water	Not available
Viscosity	5000 cps	Solubility (Other)	Hydrocarbons
Density	1.13 (relative)	VOC	<250 g/L

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Acids, bases, strong oxidizing agents

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause drowsiness or dizziness.

Skin Contact

May cause allergic skin reaction. May cause skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

May be fatal if swallowed and enters airways. May cause gastrointestinal irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Chlorinated polypropylene (Mixture)

Oral LD50 Rat 5000 mg/kg

Polyphenol antioxidant (Trade Secret)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

Inhalation LC50 Rat >165 mg/L 1 h

Magnesium oxide (1309-48-4)

Oral LD50 Rat >5000 mg/kg

Zinc oxide (1314-13-2)

Oral LD50 Rat >15000 mg/kg

Inhalation LC50 Rat >5.7 mg/L

Toluene (108-88-3)

Oral LD50 Rat >7000 mg/kg

Dermal LD50 Rabbit 12 - 14 g/kg

Inhalation LC50 Rat 30 - 35 mg/L

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Dermal LD50 Guinea pig >7246 mg/kg

Inhalation LC50 Rat 32000 ppm 4 h

Polychloroprene polymer (Mixture)

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Oral LD50 Rat >5000 mg/kg

PCBTF (98-56-6)

Oral LD50 Rat 13 g/kg

Dermal LD50 Rabbit >2 mL/kg

Inhalation LC50 Rat 33 mg/L 4 h

Immediate Effects

May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause allergic skin reaction. Causes damage to central nervous system. May cause drowsiness or dizziness.

Delayed Effects

Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure: central nervous system, blood.

Irritation/Corrosivity Data

Causes serious eye irritation.

Respiratory Sensitization

No data available.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

Magnesium oxide	1309-48-4
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
Toluene	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
Acetone	67-64-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

Central nervous system

Specific Target Organ Toxicity - Repeated Exposure

Blood, central nervous system

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415
Aspiration hazard

May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

May cause allergic skin reaction. Aspiration into the lungs may cause chemical pneumonitis.

Additional Data

No additional information available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Polyphenol antioxidant	Trade Secret
Fish:	LC50 96 h <i>Oncorhynchus mykiss</i> >0.2 mg/L [semi-static]
Algae:	EC50 72 h <i>Pseudokirchneriella subcapitata</i> >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h <i>Daphnia magna</i> >0.2 mg/L IUCLID
Toluene	108-88-3
Fish:	LC50 96 h <i>Pimephales promelas</i> 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h <i>Pimephales promelas</i> 12.6 mg/L [static]; LC50 96 h <i>Oncorhynchus mykiss</i> 5.89 - 7.81 mg/L [flow-through]; LC50 96 h <i>Oncorhynchus mykiss</i> 14.1 - 17.16 mg/L [static]; LC50 96 h <i>Oncorhynchus mykiss</i> 5.8 mg/L [semi-static]; LC50 96 h <i>Lepomis macrochirus</i> 11 - 15 mg/L [static]; LC50 96 h <i>Oryzias latipes</i> 54 mg/L [static]; LC50 96 h <i>Poecilia reticulata</i> 28.2 mg/L [semi-static]; LC50 96 h <i>Poecilia reticulata</i> 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h <i>Pseudokirchneriella subcapitata</i> >433 mg/L IUCLID; EC50 72 h <i>Pseudokirchneriella subcapitata</i> 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 5.46 - 9.83 mg/L [static] EPA; EC50 48 h <i>Daphnia magna</i> 11.5 mg/L IUCLID
Acetone	67-64-1
Fish:	LC50 96 h <i>Oncorhynchus mykiss</i> 4.74 - 6.33 mL/L; LC50 96 h <i>Pimephales promelas</i> 6210 - 8120 mg/L [static]; LC50 96 h <i>Lepomis macrochirus</i> 8300 mg/L

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [static] EPA; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID
PCBTF	98-56-6
Invertebrate:	EC50 48 h Daphnia magna 3.68 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name:Adhesives

Hazard Class: 3

UN/NA #: UN1133

Packing Group: II

Required Label(s): 3

Additional information: Special Provisions (172.102): 149, B52, IB2, T4, TP1, TP8

IATA Information:

UN#: UN1133

IMDG Information:

UN#: UN1133

TDG Information:

UN#: UN1133

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ
Acetone	67-64-1
CERCLA:	5000 lb final RQ; 2270 kg final RQ
PCBTF	98-56-6
TSCA 12b:	Section 4 , 1 % de minimus concentration

SARA Section 311/312 (40 CFR 370 Subparts B and C)
Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No
U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Magnesium oxide	1309-48-4	Yes	Yes	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity , 1/1/1991

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Magnesium oxide	1309-48-4
-----------------	-----------

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

	1 %
Zinc oxide	1314-13-2
	1 %
Toluene	108-88-3
	1 %
Acetone	67-64-1
	1 %

Component Analysis - Inventory

Chlorinated polypropylene (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Polyphenol antioxidant (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Magnesium oxide (1309-48-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Zinc oxide (1314-13-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Toluene (108-88-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Acetone (67-64-1)

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168
SDS 10-2415

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Yellow dye (2481-94-9)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

PCBTF (98-56-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	No

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2* Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

New SDS: May 13, 2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National

Safety Data Sheet

Material Name: Low VOC Bonding Adhesive 1168

SDS 10-2415

Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use