

Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

PVC Weathered Membrane Cleaner

Chemical Family

Cleaning solution

Product Use

PVC (Polyvinyl chloride) Membrane

Restrictions on Use

None known

Manufacturer Information:

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Supplier Information:

Mule-Hide Products Co., Inc 1195 Prince Hall Dr. Beloit, WI 53511

USA

Phone: 800-786-1492

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2 Serious Eye Damage/Eye Irritation - Category 2A Specific Target Organ Toxicity - Single Exposure - Category 3

GHS Label Elements

Symbol(s)





Signal Word

Danger

Hazard Statement(s)

Highly flammable liquid and vapor Causes serious eye irritation May cause respiratory irritation. May cause drowsiness or dizziness

Precautionary Statement(s)

Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08 Page 1 of 10



Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

Prevention

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Response

In case of fire: Use appropriate media to extinguish

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower

Storage

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Other Hazards

Repeated exposure may cause skin dryness or cracking.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
67-64-1	Acetone	60-100

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Page 2 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops.

Eves

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

If swallowed, get medical attention. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed

No information on significant adverse effects.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use dry chemical, carbon dioxide, alcohol-resistant foam or water spray.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors are heavier than air and may flashback.

Hazardous Combustion Products

carbon monoxide, carbon dioxide, oxides of nitrogen

Advice for firefighters

Water may be ineffective. Use water spray to cool fire fire-exposed containers.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with water spray until well after the fire is out. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Page 3 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner SDS 10-3110

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Eliminate all sources of ignition. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements, or confined areas. Stop leak if possible without personal risk. Vapor-suppressing foam may be used to control vapors. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools and equipment. Dike for later disposal. Dispose in accordance with all applicable regulations.

Environmental Precautions

Avoid release to the environment. Collect spillage.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep container tightly closed. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Since emptied containers retain material residue, follow safe handling/label warnings even after container is emptied. Use non-sparking tools. Ground any equipment used in handling.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep away from sources of ignition. Keep separated from incompatible substances.

Incompatible Materials

Strong acids, bases, oxidizing agents

Continue C. EVECCUE CONTROLS / DEDCOMM, DEGLECTION

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Acetone	67-64-1

Page 4 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

ACGIH:	250 ppm TWA	500 ppm STEL	
NIOSH:	250 ppm TWA; 590 mg/m3 TWA		
Europe:	500 ppm TWA; 1210 mg/m3 TWA		
OSHA (US):	1000 ppm TWA; 2400 mg/m3 TWA		
Mexico:	1000 ppm TWA LMPE-PPT; 2400 mg/m3 TWA LMPE-PPT		
	1260 ppm STEL [LMPE-CT]; 3000 mg/m3 STEL [LMPE-CT]		

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colorless liquid	Physical State	liquid
Odor	sweet,pungent	Color	Colorless
Odor Threshold	Not available	рН	Not available
Melting Point	-94 °C(-137.2°F)	Boiling Point	56 °C(132.8°F)
Freezing point	Not available	Evaporation Rate	6.3
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	465 °C(869°F)	Flash Point	-20 °C(-4°F)
Lower Explosive Limit	2.5	Decomposition	Not available

Page 5 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

Upper Explosive Limit	12.8	Vapor Pressure	180 mmHg
Vapor Density (air=1)	2	Specific Gravity (water=1)	Not available
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	0.79	Molecular Weight	58.08

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

Strong acids, bases, oxidizing agents

Hazardous decomposition products

Oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact

May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause allergic skin reaction.

Eye Contact

Causes serious eye irritation.

Ingestion

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea. May present an aspiration hazard. May be fatal if swallowed and enters airways.

Acute and Chronic Toxicity

Page 6 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner

SDS 10-3110

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Inhalation LC50 Rat 50100 mg/m3 8 h

Product Toxicity Data

Product Analysis LD/LC 50 Toxicity Values

Oral LD50:	Rat 5800 mg/kg
Dermal LD50:	Guinea pig >7246 mg/kg
Inhalation LC50:	Rat 32000 ppm 4 hr

Immediate Effects

Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

Causes serious eye irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Acetone	67-64-1	
ACGIH:	A4 - Not Classifiable as a Human Carcinogen	

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

Respiratory tract

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

May present an aspiration hazard. May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

Page 7 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner

Liver and/or kidney disorders

SDS 10-3110

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Acetone	67-64-1
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static]; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [static] EPA; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Component Waste Numbers

Acetone	67-64-1
RCRA:	waste number U002 (Ignitable waste)

Section 14 - TRANSPORT INFORMATION

US DOT Information: Shipping Name: Acetone

Hazard Class: 3 UN/NA #: UN1090 Packing Group: II Required Label(s): 3

Additional information: Special provisions IB2, T4, TP1

IATA Information: Shipping Name: Acetone

Hazard Class: 3 UN#: UN1090 Packing Group: II Required Label(s): 3

TDG Information: Shipping Name: Acetone

Page 8 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



Material Name: PVC Weathered Membrane Cleaner SDS 10-3110

Hazard Class: 3 UN#: UN1090 Packing Group: II Required Label(s): 3

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Acetone	67-64-1
CERCLA:	5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Acetone	67-64-1
	1 %

Component Analysis - Inventory

Acetone (67-64-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

Page 9 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08



SDS 10-3110

Material Name: PVC Weathered Membrane Cleaner

HMIS Rating

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes Nes SDS: 5/11/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use

Page 10 of 10 Issue date: 2015-05-27 Revision 1.0 Print date: 2016-09-08