

SAFETY DATA SHEET

	This safety data	sheet complies with the re	quirements of: 29CFR1910.1200	
Issue Date 11-May-2015	Revision Date 21-May-	2015	Version 1	
<u>Product identifier</u> Product Name	Mule-Hide SEBS 1 Sealant			
<u>Other means of identification</u> Product Code Synonyms	None			
<u>Recommended use of the chemica</u> Recommended Use	l and restrictions on use Sealant.			
Uses advised against	For exterior use only. Do not use	indoors.		
Details of the supplier of the safety Manufacturer Address	data sheet R.M. Lucas Company 3211 South Wood Street Chicago, Illnois 60608 (773) 523-4300	Supplier Address	Mule-Hide Products, Co., Inc. 1195 Prince Hall Drive Beloit, Wi 53511 (800) 786-1492	
Emergency telephone number Emergency Telephone	Call CHEMTREC Day or Night: Within USA and Canada: 1-800 4 Outside USA and Canada: 1-703			

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements Harmful if inhaled Causes skin irritation Causes serious eye irritation May be fatal if swallowed and enters airways Flammable liquid and vapor



Appearance Viscous

Physical state Paste/Gel

Odor Solvent (Mineral Spirits) Aromatic

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. Keep container tightly closed when product is not in use. Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

Specific treatment (see first aid information on this label) If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life
- Unknown acute toxicity

61% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Mixture

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name	Sealant and Caulk.
Synonyms	None.
Chemical nature	Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Hydrocarbon Resin	69430-35-9	30 - 40%	*
Styrene/Butadiene Copolymer	66070-58-4	20 - 30%	*
Aromatic Naptha (with <0.1% Benzene)	64742-95-6	20 - 30%	*
1,2,4 Trimethylbenzene	95-63-6	10 - 20%	*
Amorphous Silica (Silicon Dioxide)	7631-86-9	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Contains petroleum distillate. Harmful or fatal if swallowed.Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.		
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.		
Skin contact	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.		
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.		
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.		
Self-protection of the first aider	First aider: Pay attention to self-protection!.		
Most important symptoms and effects, both acute and delayed			
Symptoms	May cause skin irritation. May cause eye irritation.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

Other Information	Eliminate all ignition sour	Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).		
For emergency responders	Use personal protection r	Use personal protection recommended in Section 8.		
Environmental precautions				
Environmental precautions	Prevent product from enter	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.		
Methods and material for contain	ment and cleaning up			
Methods for containment	Contain spillage with non earth, vermiculite.	-combustible absorbent material, e	.g. sand, earth, diatomaceous	
Methods for cleaning up		terial (described just above) and tra cording to local / national regulatio		
Prevention of secondary hazards	Clean contaminated obje	cts and areas thoroughly observing	environmental regulations.	
	7. HANDLING	AND STORAGE		
Precautions for safe handling				
Advice on safe handling	Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.			
Conditions for safe storage, including any incompatibilities				
Storage Conditions	Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.			
Incompatible materials	Strong acids. Strong oxidizing agents.			
8. E	XPOSURE CONTROLS	S/PERSONAL PROTECTIO	N	
Control parameters				
Exposure Guidelines	No ACGIH or OSHA PEL is assigned to this mixture. Exposure limits for the component materials are shown below. This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA.			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³	
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	(vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO2) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³	
Appropriate engineering controls				
Engineering Controls	cross ventilation. Ventilati	ion, local (mechanical) pick-up, an ion pattern should be designed to p be sufficient to maintain asphalt va	prevent accumulation of asphalt	

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

TWA limits outlined above.

Skin and body protection Wear protective gloves and protective clothing that is resistant to chemical penetration.

determine potentially hazardous substances.

Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.		
General Hygiene Considerations	Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.		
	9. PHYSICAL AND CH	EMICAL PROPERTIES	
Information on basic physical and	d chemical properties		
Physical state	Paste/Gel		
Appearance	Viscous	Odor	Solvent (Mineral Spirits) Aromatic
Color	Clear Various	Odor threshold	1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to

Property pН Melting point/freezing point

Boiling point / boiling range Flash point **Evaporation rate** Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density **Specific Gravity** Water solubility Solubility in other solvents

Partition coefficient Autoignition temperature **Decomposition temperature** Kinematic viscosity Dynamic viscosity **Explosive properties Oxidizing properties**

Other Information

Softening point Molecular weight VOC Content (%) Density **Bulk density**

Reactivity Not applicable

Values Not applicable None / -70 °C None / -94 °F

> 154 °C / 310 °F > 40.5 °C / > 105 °F 0.1 No information available

7.0 1.6 @ 20 °C 0.3 (kPa) 5.3 1-1.1 Insoluble Soluble in aromatic and aliphatic solvents. No information available 330 °C / 626 °F No information available No information available No information available Vapor accumulation could flash or explode if ignited. None

Not applicable No information available Less than 300 g/l 8.3 to 8.5 lb/gal Not applicable

10. STABILITY AND REACTIVITY

Not applicable

Remarks • Method

Melting Point is not applicable. Freezing points are shown.

Setaflash Butly acetate = 1

Flammable above 105 degrees F and 40.5 degrees C.

Where: Air = 1 at 68 degrees F (20 degrees C) Water = 1g/ml

No data available.

Chemical stability Stable. **Possibility of Hazardous Reactions** None under normal use. Hazardous polymerization Hazardous polymerization does not occur. **Conditions to avoid**

Avoid static discharge. Avoid heat, sparks, and open flame. Incompatible materials Strong acids. Strong oxidizing agents. **Hazardous Decomposition Products** Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Toxicological testing has not been conducted for this product overall. Available toxicologic data for individualingredients are summarized below.	
Inhalation	Avoid breathing vapors or mists.	
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.	
Skin contact	May cause irritation.	
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
1,2,4 Trimethylbenzene 95-63-6	= 3400 mg/kg(Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Amorphous Silica (Silicon Dioxide) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h

Information on toxicological effects

Symptoms

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Serious eye damage/eye irritati Irritation Corrosivity Sensitization Germ cell mutagenicity Carcinogenicity	Irritating to e Not classified May cause s This product The table be	yes. yes, respiratory system and d. ensitization of susceptible does not contain any ingre ow indicates whether each		
	1 0	nt as a carcinogen.		
Chemical Name	ACGIH	IARC	NTP	OSHA

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous Silica (Silicon	-	Group 3	-	-
Dioxide)				
7631-86-9				

Legend

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen.

Reproductive toxicity None known.

Developmental Toxicity	None known.
Teratogenicity	None known.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Numerical measures of toxicity - No information available

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral)	5,268.00
ATEmix (dermal)	2,281.00
ATEmix (inhalation-dust/mist)	4.50

12. ECOLOGICAL INFORMATION

Ecotoxicity

The following table lists information related to aquatic toxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene	-	7.19 - 8.28: 96 h Pimephales	6.14: 48 h Daphnia magna mg/L
95-63-6		promelas mg/L LC50 flow-through	EC50
Amorphous Silica (Silicon Dioxide)	440: 72 h Pseudokirchneriella	5000: 96 h Brachydanio rerio mg/L	7600: 48 h Ceriodaphnia dubia
7631-86-9	subcapitata mg/L EC50	LC50 static	mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient	
1,2,4 Trimethylbenzene	3.63	
95-63-6		

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods				
Disposal of wastes	Disposal should be in accordance with applicable local, regional, national and international laws and regulations.			
Contaminated packaging	Do not reuse container.			

14. TRANSPORT INFORMATION

DOT	Regulated DOT Ground: Not regulated if shipped in containers < 119 gallons (450 liters). DOT Ground: Regulated if shipped in containers >119 gallons (450 liters).	
Proper shipping name	Combustible liquid, n.o.s (mineral spirits)	
Hazard Class	3	
Packing Group	III	

<u>TDG</u>	Regulated		
UN/ID no.	NA 1993		
Proper shipping name	Combustible liquid, n.o.s (mineral spirits)		
Hazard Class	3		
Packing Group	III		
<u>MEX</u>	Regulated		
UN/ID no.	NA 1993		
Proper shipping name	Combustible liquid, n.o.s. (mineral spirits)		
<u>ICAO (air)</u>	Regulated		
UN/ID no.	1993		
<u>IATA</u>	Regulated		
UN/ID no.	1993		
IMDG	Regulated		
UN/ID no.	1993		
RID	Not applicable in the United States.		
ADR	Not applicable in the United States.		
ADN	Not applicable in the United States.		
15. REGULATORY INFORMATION			
International Inventories TSCA	All of the components of this product are listed on the US TSCA (Toxic Substances Control		

International Inventories	
TSCA	All of the components of this product are listed on the US TSCA (Toxic Substan
	Act) Inventory or are exempt.
DSL/NDSL	All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
1,2,4 Trimethylbenzene - 95-63-6	1.0	
SARA 311/312 Hazard Categories		
Acute health hazard	Yes	
Chronic Health Hazard	Yes	
Fire hazard	Yes	
Sudden release of pressure hazard	No	
Reactive Hazard	No	

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

This product contains the following substances regulated by various State Right-to-Know regulations.

	Chemical Name	New Jersey	Massachusetts	Pennsylvania
	1,2,4 Trimethylbenzene 95-63-6	Х	Х	Х
[Amorphous Silica (Silicon Dioxide) 7631-86-9	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection -
Chronic Hazard Star Lege	nd *= Chronic	Health Hazard		
Prepared By	Prepared b	by Robert Barry		
Issue Date	11-May-20	15		
Revision Date	21-May-20	15		
Revision Note				
No information available				
<u>Disclaimer</u>				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet