

SDS 10-3105 **Material Name: Weathered Membrane Cleaner**

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Weathered Membrane Cleaner

Chemical Family

cleaner

Product Use

cleaner

Restrictions on Use

For industrial use only

Manufacturer Information:

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Supplier Information:

Mule-Hide Products Co., Inc 1195 Prince Hall Dr. Beloit, WI 53511

USA

Phone: 800-786-1492

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (lungs,brain,kidneys,nervous system)

GHS Label Elements

Symbol(s)







Signal Word

Danger

Hazard Statement(s)

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation

Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08 Page 1 of 10



Material Name: Weathered Membrane Cleaner

SDS 10-3105

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not eat, drink or smoke when using this product

Response

In case of fire: Use appropriate media to extinguish

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell IF SWALLOWED: Immediately call a POISON CENTER

Do NOT induce vomiting

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower

If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Specific treatment (see label)

Storage

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent	
64742-89-8	Solvent naphtha, petroleum, light aliphatic	60-100	

Page 2 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner SDS 10-3105

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eyes

Rinse cautiously with water for 15 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

Aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. If swallowed, get medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

Delayed

lung damage, brain damage, kidney damage, nervous system damage

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors are heavier than air and may flashback.

Hazardous Combustion Products

toxic gases: carbon monoxide, carbon dioxide.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in

Page 3 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Wear self-contained breathing apparatus and protective clothing. Use non-sparking tools and equipment. Flammable liquid: Fire or projection hazard. Vapor-suppressing foam may be used to control vapors. Eliminate all sources of ignition. All equipment used when handling the product must be grounded. Stop leak if possible without personal risk. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements, or confined areas. Dike for later disposal. Use non-sparking tools. Large spills: Keep unnecessary people away, isolate hazard area and deny entry. Prevent entry into waterways, sewers, basements, or confined areas. Dike for later disposal. Use water spray jet to minimize or disperse vapors. Runoff may create fire or explosion hazard. Absorb with earth, sand or other non-combustible material and transfer to container. Dispose in accordance with all applicable federal, state/regional and local laws and regulations.

Environmental Precautions

Avoid release to the environment. Collect spillage.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Highly flammable liquid and vapor. Keep container tightly closed. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from incompatible materials. Do not breathe vapor. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. Do not ingest. KEEP OUT OF REACH OF CHILDREN.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Store in accordance with all current regulations and standards. Store in a cool dry place. Keep away from sources of ignition. Ground/Bond container and receiving equipment. Keep away from incompatible materials.

Incompatible Materials

Page 4 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

Strong acids, alkalies, oxidizing agents, chlorine, oxygen

SDS 10-3105

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

ACGIH, NIOSH, EU, OSHA (US) and Mexico have not developed exposure limits for any of this product's components

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	clear liquid	Physical State	liquid	
Odor	hydrocarbon odor	Color	clear	
Odor Threshold	Not available	рН	Not available	
Melting Point	Not available	Boiling Point	118 - 150 °C	
Freezing point	Not available	Evaporation Rate	1	
Boiling Point Range	Not available	Flammability (solid, gas)	Not available	
Autoignition	320 °C(608°F)	Flash Point	18 °C(64.4°F)	
Lower Explosive Limit	0.9	Decomposition	Not available	
Upper Explosive Limit	7	Vapor Pressure	11.5 mmHg	

Page 5 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

Vapor Density (air=1)	4	Specific Gravity (water=1)	Not available	
Water Solubility	negligible	Partition coefficient: n-octanol/water	Not available	
Viscosity	Not available	Solubility (Other)	Not available	
Density	0.74 - 0.76	voc	100 %	

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Avoid contact with incompatible materials.

Incompatible Materials

Strong acids, alkalies, oxidizing agents, chlorine, oxygen

Hazardous decomposition products

Releases toxic gases: carbon monoxide, carbon dioxide.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Eve Contact

May cause eye irritation.

Ingestion

May cause irritation of the mouth and throat. May cause central nervous system depression. Aspiration Hazard. May be fatal if swallowed and enters airways.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Page 6 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

Oral LD50 Mouse 5000 mg/kg Dermal LD50 Rabbit 3000 mg/kg

Product Toxicity Data

Product Analysis LD/LC 50 Toxicity Values

Oral LD50:	Rat >2000 ring/kg LD50				
Dermal LD50:	Rat 2000 mg/kg				
Inhalation LC50:	Rat >5000 ppm 1 hour LD50				

Immediate Effects

Causes skin irritation. May cause drowsiness or dizziness.

Delayed Effects

Lung damage, brain damage, kidney damage, liver damage, nervous system damage

Irritation/Corrosivity Data

Causes skin irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

Central nervous system

Specific Target Organ Toxicity - Repeated Exposure

lungs, brain, kidneys, liver, nervous system

Aspiration hazard

Aspiration Hazard. May be fatal if swallowed and enters airways.

Medical Conditions Aggravated by Exposure

Skin disorders, respiratory disorders, liver disorders, kidney disorders, central nervous system disorders

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Page 7 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

Solvent naphtha, petroleum, light aliphatic	64742-89-8			
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID			

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. Subject to disposal regulations. U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: Paint Related Material

Hazard Class: 3 UN/NA #: UN1263 Packing Group: II Required Label(s): 3

Additional information: Special provisions 149, B52, IB2, T4, TP1, TP8

IATA Information:

Shipping Name: Paint Related Material

Hazard Class: 3 UN#: UN1263 Packing Group: II Required Label(s): 3

TDG Information:

Shipping Name: Paint Related Material

Hazard Class: 3 UN#: UN1263 Packing Group: II Required Label(s): 3

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Page 8 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

Component Analysis - Inventory

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2* Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes New SDS: 5/6/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -

Page 9 of 10 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-09-08



Material Name: Weathered Membrane Cleaner

SDS 10-3105

Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use