

---

**Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

---

**Material Name:** Mule-Hide Black Lap Sealant**Synonym:** Industrial Sealant**Chemical Family:** Solvent Based Sealant**Product Use:** Sealant for EPDM Single-Ply Roofing Membranes**Restrictions on Use:** For industrial use only.**Manufacturer Information**

Carlisle SynTec

1285 Ritner Highway

Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

---

**Section 2 - HAZARDS IDENTIFICATION**

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 2

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (lungs, central nervous system)

**GHS Label Elements****Symbol(s)****Signal Word**

Danger

**Hazard Statement(s)**

Highly flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

**Precautionary Statement(s)****Prevention**

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**

**SDS 10-3415**

Keep container tightly closed  
 Keep away from heat/sparks/open flame/hot surfaces - No smoking  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting equipment  
 Take precautionary measures against static discharge  
 Use only non-sparking tools  
 Use only outdoors or in a well-ventilated area  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Do not breathe dust/fume/gas/mist/vapours/spray  
 Wash thoroughly after handling  
 Do not eat, drink or smoke when using this product

**Response**

In case of fire: Use appropriate media to extinguish  
 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 Call a POISON CENTER or doctor if you feel unwell  
 Specific treatment (see label)

**Storage**

Store in a well-ventilated place. Keep cool  
 Keep container tightly closed  
 Store locked up

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

**Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

CAS	Component Name	Percent
Not applicable	Ground coal	1-5
Trade Secret	Silica compound	1-5
Trade Secret	Severely hydrotreated paraffinic oil	3-7
1317-65-3	Limestone	10-30
Trade Secret	Carbon compound	1-5
Trade Secret	Polyphenol antioxidant	0.1-1
64742-89-8	Naphtha, petroleum, light aliphatic	10-30

Material Name: Mule-Hide Black Lap Sealant

SDS 10-3415

Trade Secret	Polybutene	1-5
Mixture	Terpene phenolic resin	1-5
12001-26-2	Mica	0.1-1
64742-88-7	Solvent naphtha, petroleum, medium aliphatic	10-30

---

### Section 4 - FIRST AID MEASURES

---

**Description of Necessary Measures**

IF exposed or concerned: Get medical advice/attention.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

**Skin**

Remove/Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention.

**Eyes**

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

**Ingestion**

If swallowed, get medical attention. Do NOT induce vomiting.

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically and supportively.

**Most Important Symptoms/Effects****Acute**

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause gastrointestinal irritation.

**Delayed**

Causes damage to organs through prolonged or repeated exposure: lungs, central nervous system.

---

### Section 5 - FIRE FIGHTING MEASURES

---

**Extinguishing Media****Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide. Water may be ineffective. Use water spray to keep containers cool.

**Unsuitable Extinguishing Media**

Do not use high-pressure water streams.



## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**

**SDS 10-3415**

### **Special Hazards Arising from the Chemical**

Can burn and explode easily when exposed to open flames or high heat.

### **Hazardous Combustion Products**

Oxides of carbon, oxides of nitrogen

### **Fire Fighting Measures**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

---

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

---

### **Personal Precautions, Protective Equipment and Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8.

### **Methods and Materials for Containment and Cleaning Up**

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Dike for later disposal.

### **Environmental Precautions**

Avoid release to the environment.

---

## **Section 7 - HANDLING AND STORAGE**

---

### **Precautions for Safe Handling**

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Do not eat or drink when using this product. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wash contaminated clothing before reuse. **KEEP OUT OF REACH OF CHILDREN.**

### **Conditions for Safe Storage, Including any Incompatibilities**

Store in a well-ventilated place. Keep cool

Keep container tightly closed

Store locked up

Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

### **Incompatible Materials**

Strong oxidizing agents, acids, bases

---

## **Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

### **Component Exposure Limits**

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**

<b>Silica compound</b>	Trade Secret	
OSHA (US):	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA)	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	
<b>Limestone</b>	1317-65-3	
NIOSH:	10 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable dust	
OSHA (US):	15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	20 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Carbon compound</b>	Trade Secret	
ACGIH:	3 mg/m <sup>3</sup> TWA inhalable fraction	
NIOSH:	3.5 mg/m <sup>3</sup> TWA; 0.1 mg/m <sup>3</sup> TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons) as PAH	
	1750 mg/m <sup>3</sup> IDLH	
OSHA (US):	3.5 mg/m <sup>3</sup> TWA	
Mexico:	3.5 mg/m <sup>3</sup> TWA LMPE-PPT	7 mg/m <sup>3</sup> STEL [LMPE-CT]
<b>Mica</b>	12001-26-2	
ACGIH:	3 mg/m <sup>3</sup> TWA respirable fraction	
NIOSH:	3 mg/m <sup>3</sup> TWA (containing <1% Quartz) respirable dust	1500 mg/m <sup>3</sup> IDLH (containing <1% Quartz)
OSHA (US):	20 mppcf TWA (<1% Crystalline silica)	
Mexico:	3 mg/m <sup>3</sup> TWA LMPE-PPT respirable fraction	
<b>Silica, crystalline</b>	14808-60-7	
ACGIH:	0.025 mg/m <sup>3</sup> TWA respirable fraction	
NIOSH:	0.05 mg/m <sup>3</sup> TWA respirable dust	50 mg/m <sup>3</sup> IDLH respirable dust
OSHA (US):	((30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA) total dust; ((250)/(%SiO <sub>2</sub> + 5) mppcf TWA) respirable fraction; ((10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA) respirable fraction	

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**

Mexico:	0.1 mg/m <sup>3</sup> TWA LMPE-PPT respirable fraction
---------	--

**Biological limit value**

There are no biological limit values for any of this product's components.

**Engineering Controls**

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

**Individual Protection Measures, such as Personal Protective Equipment**
**Eye/face protection**

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**Skin Protection**

Wear appropriate work clothing. Wear protective shoes. Recommended material: protective skin cream.

**Respiratory Protection**

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**Glove Recommendations**

Wear appropriate chemical resistant gloves.

---

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	viscous paste	<b>Physical State</b>	liquid
<b>Odor</b>	hydrocarbon	<b>Color</b>	black
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	<18 °C (< 0 °F)	<b>Boiling Point</b>	119 - 185 °C (246-365 °F)
<b>Freezing point</b>	<18 °C	<b>Evaporation Rate</b>	3.5
<b>Boiling Point Range</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition</b>	230 °C (446 °F)	<b>Flash Point</b>	4.4 °C [TCC] (40 °F)
<b>Lower Explosive Limit</b>	0.8 %	<b>Decomposition</b>	Not available
<b>Upper Explosive Limit</b>	6.7 %	<b>Vapor Pressure</b>	8.27 mmHg
<b>Vapor Density (air=1)</b>	4	<b>Specific Gravity (water=1)</b>	1.03 - 1.04
<b>Water Solubility</b>	negligible	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	1100000 cps	<b>Solubility (Other)</b>	hydrocarbons

Material Name: Mule-Hide Black Lap Sealant

SDS 10-3415

Density	Not available	VOC	390 - 400 g/L
---------	---------------	-----	---------------

**Other Information**

No additional information available.

---

**Section 10 - STABILITY AND REACTIVITY**

---

**Reactivity**

No reactivity hazard is expected.

**Chemical Stability**

Stable under normal conditions of use.

**Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

**Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

**Incompatible Materials**

Strong oxidizing agents, acids, bases

**Hazardous decomposition products**

Oxides of carbon, oxides of nitrogen

---

**Section 11 - TOXICOLOGICAL INFORMATION**

---

**Information on Likely Routes of Exposure****Inhalation**

May cause respiratory irritation.

**Skin Contact**

Causes skin irritation.

**Eye Contact**

Causes serious eye irritation.

**Ingestion**

May cause gastrointestinal irritation.

**Acute and Chronic Toxicity****Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Severely hydrotreated paraffinic oil (Trade Secret)

Oral LD50 Rat &gt;5000 mg/kg

Dermal LD50 Rabbit &gt;2000 mg/kg

Carbon compound (Trade Secret)

Oral LD50 Rat &gt;15400 mg/kg

**Material Name: Mule-Hide Black Lap Sealant**

**SDS 10-3415**

Polyphenol antioxidant (Trade Secret)  
 Oral LD50 Rat >200 mg/kg  
 Dermal LD50 Rabbit >5010 mg/kg

Naphtha, petroleum, light aliphatic (64742-89-8)  
 Oral LD50 Mouse 5000 mg/kg  
 Dermal LD50 Rabbit 3000 mg/kg

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)  
 Oral LD50 Rat >5000 mg/kg  
 Dermal LD50 Rabbit 3000 mg/kg

Silica, crystalline (14808-60-7)  
 Oral LD50 Rat 500 mg/kg

**Immediate Effects**

Cause skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause gastrointestinal irritation.

**Delayed Effects**

Causes damage to organs through prolonged or repeated exposure: lungs, central nervous system.

**Irritation/Corrosivity Data**

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

**Respiratory Sensitization**

No data available.

**Dermal Sensitization**

It may cause sensitization in some individuals.

**Component Carcinogenicity**

<b>Silica compound</b>	Trade Secret
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))
<b>Carbon compound</b>	Trade Secret
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man, inhalable fraction)
OSHA:	Present



## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**

<b>Silica, crystalline</b>	14808-60-7
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)
OSHA:	Present (respirable size)

**Germ Cell Mutagenicity**

No data available.

**Reproductive Toxicity**

No data available.

**Specific Target Organ Toxicity - Single Exposure**

May affect the central nervous system: drowsiness, dizziness.

**Specific Target Organ Toxicity - Repeated Exposure**

May cause damage to organs through prolonged or repeated exposure: lungs, central nervous system.

**Aspiration hazard**

May cause aspiration hazard.

**Medical Conditions Aggravated by Exposure**

May cause allergic skin reaction. Aspiration into the lungs may cause chemical pneumonitis.

**Additional Data**

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

---

### Section 12 - ECOLOGICAL INFORMATION

---

**Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity**

<b>Severely hydrotreated paraffinic oil</b>	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
<b>Polyphenol antioxidant</b>	Trade Secret

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**

Fish:	LC50 96 h Oncorhynchus mykiss >0.2 mg/L [semi-static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >0.2 mg/L IUCLID
<b>Naphtha, petroleum, light aliphatic</b>	64742-89-8
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
<b>Solvent naphtha, petroleum, medium aliphatic</b>	64742-88-7
Fish:	LC50 96 h Pimephales promelas 800 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 450 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >100 mg/L IUCLID

**Persistence and Degradability**

No information available for the product.

**Bioaccumulative Potential**

No information available for the product.

**Mobility**

No information available for the product.

**Other Toxicity**

No additional information available.

### Section 13 - DISPOSAL CONSIDERATIONS

**Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Section 14 - TRANSPORT INFORMATION

**US DOT Information:**
**Shipping Name:** ADHESIVES

**Hazard Class:** 3



## Safety Data Sheet

**Material Name:** Mule-Hide Black Lap Sealant

**SDS 10-3415**

**UN/NA #:** UN1133

**Packing Group:** II

**Required Label(s):** < 0.3 gal (limited quantity)

**IATA Information:**

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

**UN#:** UN1133

**Packing Group:** II

**Required Label(s):** < 0.3 gal (limited quantity)

**TDG Information:**

**Shipping Name:**ADHESIVES

**Hazard Class:** 3

**UN#:** UN1133

**Packing Group:** II

**Required Label(s):**

---

### Section 15 - REGULATORY INFORMATION

---

**U.S. Federal Regulations**

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

**SARA Section 311/312 (40 CFR 370 Subparts B and C)**

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Silica compound	Trade Secret	No	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Carbon compound	Trade Secret	Yes	Yes	Yes	Yes	Yes
Mica	12001-26-2	Yes	Yes	Yes	Yes	Yes
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	No	No	No	Yes	No
Silica, crystalline	14808-60-7	No	Yes	Yes	Yes	Yes

**The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

**WARNING!** This product contains a chemical known to the state of California to cause cancer

Carbon compound	Trade Secret
-----------------	--------------

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**

Carc:	carcinogen , initial date 2/21/03 (airborne, unbound particles of respirable size)
Silica, crystalline	14808-60-7
Carc:	carcinogen , initial date 10/1/88 (airborne particles of respirable size)

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Carbon compound	Trade Secret
	1 %
Mica	12001-26-2
	1 %
Silica, crystalline	14808-60-7
	1 %

**Component Analysis - Inventory**

Silica compound (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Severely hydrotreated paraffinic oil (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	No

Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Carbon compound (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Safety Data Sheet

**Material Name: Mule-Hide Black Lap Sealant**
**SDS 10-3415**
**Polyphenol antioxidant (Trade Secret)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

**Naphtha, petroleum, light aliphatic (64742-89-8)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

**Polybutene (Trade Secret)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

**Mica (12001-26-2)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

**Solvent naphtha, petroleum, medium aliphatic (64742-88-7)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

**Silica, crystalline (14808-60-7)**

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes



## Safety Data Sheet

Material Name: Mule-Hide Black Lap Sealant

SDS 10-3415

### Section 16 - OTHER INFORMATION

---

#### HMIS Rating

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

#### NFPA Ratings

Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

#### Summary of Changes

Revision Date: June 1, 2018

Revision Note: General Update

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

#### Other Information

##### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.