



Product Data Sheet

MULE-HIDE PVC COATED METAL

PRODUCT DESCRIPTION

Mule-Hide PVC Coated Metal is a 24-gauge galvanized steel sheet that is coated with a layer of 0.035" non-reinforced PVC flashing.

BASIC USES

PVC Coated Metal is cut into the appropriate width and used to fabricate metal drip edges or other roof perimeter edging profiles. PVC membrane may be welded directly to the coated metal edging, eliminating the need to strip in the metal with a separate piece of membrane.



TYPICAL PHYSICAL PROPERTIES

Typical Properties and Characteristics*	
Sheet Size	4' x 10' (1.2m by 3.0 m)
Weight	1.1 lf/ft ² (5.4 kg/m ²)
Color	White, Gray & Tan
Flashing Thickness	.035" (0.9 mm) nominal
Steel Thickness	.024" (0.6 mm) nominal (24 ga)
Steel Type	Hot Dipped Galvanized – G90
Packaging	10 sheets per pallet

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

LEED Information	
Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Location	Scranton, PA
Solar Reflectance Index	White: 111 Gray: 43 Tan: 50

BENEFITS & SUPPLEMENTAL STATEMENTS

- Allows direct welding of PVC membrane to metal
- Easy to cut and form for creating a variety of edge sizes and shapes
- Available in white, gray and tan colors
- Matches membrane color to create a uniform appearance

INSTALLATION INSTRUCTIONS

1. Install PVC coated metal with 1/8" to 1/4" (3 to 6 mm) wide joints between adjoining sections.
2. Install 2" wide (5 cm) duct tape over joints in PVC metal (to act as a bond breaker).
3. Heat-weld a minimum 6" wide (15.5 cm) strip of PVC non-reinforced flashing membrane over joint.
4. Position PVC reinforced membrane and heat-weld to PVC clad metal achieving a min 1 1/2" wide weld.

Review Mule-Hide specifications and details for additional installation information.

STORAGE & HANDLING

Store coated metal in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins.

PRECAUTIONS

PVC Coated Metal that has been exposed to the weather must be prepared with Weathered Membrane Cleaner prior to hot-air welding.

Do not allow membrane side of PVC Coated Metal to come in contact with asphalt, coal tar pitch,

Product Data Sheet

MULE-HIDE PVC COATED METAL

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.