



SEBS SEAM SEALER

PRODUCT DESCRIPTION

Mule-Hide SEBS Seam Sealer is a premium synthetic rubber based sealant and caulk. It is intended for flashing, sealing and repairing metal roofs, built-up roofing, modified bitumen, TPO and many other single ply systems. Ideal for caulking termination bars, metal flashings and fasteners. SEBS Seam Sealer is strong, elastic, and adheres to most common roofing materials. SEBS Seam Sealer is available in two grades, a gun grade intended for pump and wand application, and a semi-self leveling, brush grade mastic.

SEBS Seam Sealer is manufactured from a 100% synthetic rubber base to a mastic or semi-mastic viscosity. It contains no asphalt or other bituminous material. Formulated for application by trowel, brush or caulking gun. SEBS Seam Sealer contains anti-oxidants and light-stabilizers for extended life and reinforcing fibers that add strength and durability.

BASIC USES

SEBS Seam Sealer is used for flashing, sealing and repairing metal roofs, built-up roofing, modified bitumen, TPO and many other single-ply systems. This product is ideal for caulking termination bars, metal flashings and fasteners.

TYPICAL PHYSICAL PROPERTIES

Physical Property*	Test Method	Value
Viscosity	ASTM D 2196	500,000 cps
Solids by Weight	ASTM D 1644	53%
Solids by Volume	ASTM D 2697	67%
Weight per Gallon	ASTM D 1147	7.8 lbs.
Tensile Strength	ASTM D 2370	1,600 psi
Elongation	ASTM D 2370	300%
Flash Point	ASTM D 56	103°F (39°C)

* Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

PACKAGING

Container sizes: 30 oz tubes, 3 gallon, 5 gallon and 55 gallon

Colors

White

APPLICATION INSTRUCTIONS

1. Use SEBS Seam Sealer as it comes from the container with a trowel, chip brush or caulking gun.
2. Surface must be clean and free of dirt, oil, grease or corrosive particles.
3. Roof surfaces must be dry. Even when the surfaces appear dry, moisture may be trapped in the roof, deck or insulation.
4. A moisture scan is recommended prior to application.
5. SEBS Seam Sealer will adhere to wet and underwater surfaces when used for repairs only. When used to install the roof system, surfaces must be dry.
6. Apply ¼" thick and taper edges when possible.
7. When application is with a caulking gun, apply a bead between ¼" to ½" in diameter.

Product Data Sheet

MULE-HIDE SEBS SEAM SEALER

APPLICATION INSTRUCTIONS (cont.)

8. Application of the SEBS Seam Sealer when ambient air temperature is within 5°F of dew point is not recommended.
9. When applying SEBS Seam Sealer over single ply membranes, consult membrane manufacturer to ensure compatibility.
10. SEBS Seam Sealer may be left exposed or top coated with SEBS Roof Coating or SEBS+ Roof Coating. If coating, allow to dry till the next day prior to coating.

Note: When using on EPDM roofs, swelling of the EPDM membrane may occur. This product is not recommended for use with non-Elvaloy-based PVC.

PRECAUTIONS

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Keep away from heat and open flames.

Avoid prolonged contact with skin or inhalation of fumes. A NIOSH approved respirator with organic vapor cartridges is recommended.

Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. For professional use only. Read SDS prior to use.

California Proposition 65 Warning: This product may contain chemicals know to the State of California to cause cancer, birth defects and/or reproductive harm.

CLEAN UP

Clean up with naphtha.

STORAGE & HANDLING

Shelf Life: Two years from date of manufacture in unopened container.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.