



Product Data Sheet

MULE-HIDE SEAL-FAST® PRIMER

PRODUCT DESCRIPTION

Mule-Hide Seal-Fast® Primer is a solvent based primer specifically formulated to prime surfaces to be bonded with Seal-Fast® Tape or Seal-Fast® Fabric Tape in temperatures below 40°F.

Seal-Fast® Primer is based on a VOC exempt solvent that is infused with a blend of elastomers and resins.

BASIC USES

Mule-Hide Seal-Fast® Primer is used to ensure proper adhesion when installing Seal-Fast® Tape or Seal-Fast® Fabric Tape in temperatures below 40°F or when the surface quality is questionable. Seal-Fast® Primer is also used on mortar, porous surfaces and granulated surfaces (granules must be removed).

Do not apply Seal-Fast® Primer to PVC based materials

TYPICAL PHYSICAL PROPERTIES

Description	Value
Flash Point	110°F (43°C)
Application Temperature	-20°F to 205°F
Viscosity	135 to 152 cps
Weight	6 lbs. per gallon
Packaging	12 - 14 oz. spray cans per carton 12 – 1 quart cans per carton



COVERAGE RATES

One quart will cover approximately 75 square feet, depending on surface porosity and method of application.

INSTALLATION INSTRUCTIONS

Use Seal-Fast® Primer when surface temperatures are below 40°F or when surface quality is questionable.

1. All surfaces are to be thoroughly cleaned and dry prior to application.
2. On granulated surfaces, granules must be removed prior to application.
3. Shake spray can well before using, or thoroughly stir product in quart can.
4. Spray, roll or brush onto surface.
5. Apply product as a thin coat over surface.
6. Do not allow product to pool.
7. Allow Seal-Fast® Primer to dry completely before applying Seal-Fast® Tapes.

Do not apply Seal-Fast® Primer to PVC based materials

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

Product Data Sheet

MULE-HIDE SEAL-FAST[®] PRIMER

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.