



# Product Data Sheet

## MULE-HIDE Si CLEANING SOLVENT

### PRODUCT DESCRIPTION

Mule-Hide Si Cleaning Solvent is a high flash aromatic solvent that may be used to clean tools and equipment.

### BASIC USES

Mule-Hide Si Cleaning Solvent is suitable for cleanup of asphalt, thermoplastic and silicone based products.



### TYPICAL PHYSICAL PROPERTIES

Physical Property	Test Method	Value
Viscosity	ASTM D 2196	50 cps
Solids by Weight	ASTM D 1644	0%
Solids by Volume	ASTM D 2697	0%
Weight per Gallon	ASTM D 1147	7.22 lbs.
Flash Point	ASTM D 56	103°F (39°C)
VOC (7000 standard)	EPA 24	< 865 g/l
Color	----	Clear

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

### PACKAGING

Container sizes: 1 gallon and 5 gallon

### APPLICATION INSTRUCTIONS

1. Do not use on skin.
2. Apply to rag and wipe surface clean or soak tools overnight.
3. For outdoor use only

Application instructions are basic guidelines only.

### PRECAUTIONS

#### **WARNING! COMBUSTIBLE LIQUID AND VAPOR**

Contains petroleum distillates. Keep away from heat and open flames.

Contact with skin may cause redness and a rash. If skin contact occurs, wash with soap and water immediately.

Avoid prolonged contact with, or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended.

If swallowed, do not induce vomiting. Contact medical personnel immediately.

Keep out of reach of children. For professional use only. Read SDS prior to use.

**California Proposition 65 Warning:** This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

# Product Data Sheet

MULE-HIDE Si CLEANING SOLVENT

---

## **STORAGE & HANDLING**

Two years from date of manufacture with proper storage.

Job site storage in excess of 90°F (32°C) may affect product shelf life. Should the Si Cleaning Solvent be stored at temperatures lower than 60°F (15°C), restore to room temperature prior to use.

## **PROTECTION & SAFETY**

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

## **ADDITIONAL INFORMATION**

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

## **DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.