



SEAL-FAST® FABRIC TAPE

PRODUCT DESCRIPTION

Revision Date: April 29, 2019

Seal-Fast® Fabric Tape is a butyl hybrid pressure sensitive adhesive tape, which remains flexible even in cold temperatures. The fabric facer is designed to be coated to match the surrounding roofing surface.

BASIC USES

Seal-Fast® Fabric Tape may be used on metal roofs to strip in side laps, end laps, and other penetrations prior to the application of a Mule-Hide Coating System. Seal-Fast® Fabric Tape may also be used on EPDM, TPO, CSPE/Hypalon, CPE, SBS, APP modified, asphalt BURs, coal tar BURs, all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry and OSB. This product may be used to repair gutters, chimney flashings, and metal roofs on mobile homes and transport vehicles. Seal-Fast® Tape makes a permanent watertight seal. Can be installed in temperatures down to 20°F (with EPDM Tape Primer).

Seal-Fast® Fabric Tape must be coated.

TYPICAL PHYSICAL PROPERTIES

Physical Property	Test Method	Value*
Thickness w/o liner	ASTM D1777	26 mils
Tensile Breaking Strength MD/CD	ASTM D882	15 lbf/in
Elongation	ASTM D882	>700%
Puncture Resistance		
- Drop Dart	ASTM D1709 Method A	>500 g
- Penetration Resistance	ASTM F1306	4.5 lbf
WVTR @ 73°F & 50% rh	ASTM E96-B	<0.02g / 100in ² /24 hrs
Adhesion to Stainless Steel	PSTC-1	20 lbf/in
Permeance @ 73°F & 50% rh	ASTM E96-B	<0.05 perms
Low Temperature Flexibility	ASTM D1970	Excellent
UV Resistance	ASTM G154 Cycle 1	No degradation No loss of peel strength
Application Temperature	---	20°F to 170°F
Shelf Life	---	5 years
Dimensional Stability	Resistance to movement with temperature change	Excellent

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

PACKAGING

Available in rolls 6" x 25'

SEAL-FAST® FABRIC TAPE

INSTALLATION INSTRUCTIONS

SURFACE PREPARATION

1. Surface must be clean and dry, free of loose rust and scale, dust, talc and dirt.
2. Oil, grease and other contaminants must be removed with Weathered Membrane Cleaner or suitable solvent/cleaner.
3. For older plastic roofs, score surface with sand cloth and wipe away dust.

APPLICATION

1. Install Seal-Fast® Tape over repair area, remove plastic liner gradually to prevent contamination of adhesive prior to application.
2. Rub or roll with pressure (preferably with a steel roller) to activate the bonding process.
3. Seal-Fast® Tape may be applied to clean, dry surfaces from 20°F to 170°F.
4. For low temperature application (below 40°F down to 20°F) treat surface with EPDM Tape Primer prior to application and maintain tape at room temperature (+60°F) prior to application.
5. Apply roof coating to fabric surface of tape.

STORAGE & HANDLING

Shelf Life: Five years with proper storage.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.