

RHINO BOND PLATE AND APPROVED FASTENER CENTERED ON STRUCTURAL PURLINS. SPACED 6 INCHES ON CENTER

MINIMUM 3" LAP WITH MINIMUM 1 1/2" WIDE HOT AIR WELD

WOOD NAILERS REQUIRED BETWEEN RIBS AT ALL EAVES. ADDITIONAL NAILERS AS REQUIRED TO MATCH HEIGHT OF NEW INSULATION.

NOTES:

1. THIS SYSTEM MUST HAVE WRITTEN APPROVAL FROM MULE-HIDE TECHNICAL DEPARTMENT.
2. TPO SHEETS MAY NOT END ON FASTENER PLATES.

OPTION B: MEMBRANE PARALLEL TO SLOPE

MULE-HIDE 3" STRESS PLATE AND APPROVED FASTENER - 5 FASTENERS PER 4'X8' BOARD

APPROVED COVERBOARD

FLUTE FILLER TO MATCH HEIGHT OF EXISTING STANDING SEAMS

RHINO BOND MECHANICALLY ATTACHED WINDS ZONES 101-120 MPH

SYSTEMS:
RHINO BOND METAL RETROFIT
TPO MECHANICALLY FASTENED

DETAIL NO.:

MMRR-305RT

REVISION DATE: 02/2018

**MULE-HIDE
PRODUCTS CO., INC.**