



WALL COATING MATERIAL-ONLY LIMITED WARRANTY APPLICATION

Mule-Hide Products Co., Inc. | 800-786-1492 | Fax: 888-218-7838 | mulehidewarranties@mulehide.com

National Support Center, 1195 Prince Hall Drive, Beloit, WI 53511

PROJECT NAME:

Building Name: _____

Street: _____

City: _____ State: _____ Zip: _____

Architect/Consultant: _____

Phone: _____

INSTALLING CONTRACTOR NAME:

Company Name: _____

Street: _____

City: _____ State: _____ Zip: _____

Phone: _____ Fax: _____

Person Completing Application: _____

Mule-Hide Applicator Number: _____

BUILDING OWNER:

Name: _____

Contact Name: _____

Phone: _____

DISTRIBUTOR INFORMATION:

Distributor Name: _____

City: _____ State: _____

Salesman: _____

PROJECT START DATE: _____ PROJECTED/ACTUAL COMPLETION DATE: _____

WARRANTY TYPES AND CHARGES

WARRANTY TYPE	LENGTH	BUILDING TYPE	PRICE PER S.F.		SIZE (S.F.)	=	COST
Material	5 Years	Commercial	N/A	X		=	FREE <i>(DISTRIBUTOR INVOICES REQUIRED)</i>
Material	10 Years	Commercial	N/A	X		=	\$100.00 Flat Fee <i>(DISTRIBUTOR INVOICES REQUIRED)</i>

MATERIALS REQUIRED

5-Year - Two (2) coats of A-400-W at 1 gallon per 100 square feet. Total two (2) gallons per 100 square feet. The first coat shall be applied at the minimum rate of 1 gal per 100 square feet with a maximum rate not to exceed 1.5 gal per 100 square feet. After a minimum of 12 hours cure time, but before 72 hours, apply the second coat of A-400-W perpendicular to the first coat at the same minimum rate of 1 gal per 100 square feet. The finished coverage must be a minimum rate of 2 gal per 100 square feet.

10-Year - Three (3) coats of A-400-W at 1 gallon per 100 square feet. Total three (3) gallons per 100 square feet. The first coat shall be applied at the minimum rate of 1 gal per 100 square feet with a maximum rate not to exceed 1.5 gal per 100 square feet. After a minimum of 12 hours cure time, but before 72 hours, apply the second coat of A-400-W perpendicular to the first coat at the same minimum rate of 1 gallon per 100 square feet. Allow a minimum of 12 hours cure time, but before 72 hours apply a third coat at the same minimum rate of 1 gallon per 100 square feet. The finished coverage must be a minimum rate of 3 gal per 100 square feet.

Notes:

- At 1 gallon per square, the wet film thickness is 16 mils, and dry film thickness is 8 mils. These rates can be used to calculate wet and dry film thicknesses for other application rates.
- Surface must be properly cleaned with 115 Cleaner and rinsed well.
- Treat all cracks larger than 1/16" up to a maximum width of 1/8" with A-200 FLASHING GRADE and feather all edges.

GALLONS USED

115 Cleaner: _____ A-200 Flashing Grade: _____ A-400-W: _____

MULE-HIDE REQUIRES THAT ALL MATERIAL INVOICES BE PROVIDED FOR REVIEW PRIOR TO WARRANTY ISSUANCE

Warranty applications must be sent in for approval before the start of the project. Mule-Hide reserves the right to not offer warranties on projects completed prior to the receipt of a warranty application. Warranties must be executed within 90 days of roof completion. Any warranty issued by Mule-Hide Products Co., Inc. will be based upon the accuracy and completeness of the information contained in this warranty application.

ELIGIBLE CONTRACTOR SIGNATURE (MUST BE AN OFFICER OF THE COMPANY)

By _____ Title _____ Date _____