

1 PLY INSTALLATION

NOTES:

1. AN AREA DIVIDER IS A RAISED DOUBLE WOOD MEMBER THAT IS PROPERLY ANCHORED TO THE ROOF DECK. AREA DIVIDERS SHOULD NEVER RESTRICT THE FLOW OF WATER.
2. FLASHING REQUIREMENTS TYPICAL FOR BOTH SIDES OF THE AREA DIVIDER.
3. REFER TO THE SHEET METAL SECTION OF THE NRCA ROOFING AND WATERPROOFING MANUAL FOR JOINERY AND SECUREMENT OPTIONS FOR SHEET METAL.

FLASHING MAY BE SET IN A BED OF M-H MOD BIT FLASHING ADHESIVE OR HOT AIR WELDED. THE 4" TURN-UP OF THE CAP SHEET MUST BE SOFTENED WITH HOT AIR TO EXPOSE ASPHALT OR COATED WITH M-H MOD BIT FLASHING ADHESIVE PRIOR TO APPLICATION OF THE CAP SHEET FLASHING MATERIAL.

APPROVED COVERBOARD, OVERLAY, APPROVED INSULATION OR OTHER APPROVED SUBSTRATE.

INSULATION

8" [200 mm] MINIMUM FLASHING HEIGHT ON LOW SIDE

6" MIN.

SHEET METAL AREA DIVIDER COVER

GASKETED FASTENERS

MULE-HIDE SA-SBS CAP SHEET OR SA-APP CAP SHEET

CAP SHEET ATTACHMENT 12" O.C. MAX.

4" MIN.

ROOF DECK

WOOD NAILERS

**BASE FLASHING - AREA DIVIDER
OPTION 1**

SELF-ADHERING MOD BIT SYSTEMS

DETAIL NO.:

MH-MB-AD1

**MULE-HIDE
PRODUCTS CO.,INC.
2003**