


## 2 PLY INSTALLATION

**NOTES:**

1. AN AREA DIVIDER IS A RAISED DOUBLE WOOD MEMBER THAT IS PROPERLY ANCHORED TO THE ROOF DECK. AREA DIVIDERS SHOULD NEVER RESTRICT THE FLOW OF WATER.
2. FLASHING REQUIREMENTS TYPICAL FOR BOTH SIDES OF THE AREA DIVIDER.
3. REFER TO THE SHEET METAL SECTION OF THE NRCA ROOFING AND WATERPROOFING MANUAL FOR JOINERY AND SECUREMENT OPTIONS FOR SHEET METAL.



FLASHING MAY BE SET IN A BED OF M-H MOD BIT FLASHING ADHESIVE OR HOT AIR WELDED. THE 4" TURN-UP OF THE CAP SHEET MUST BE SOFTENED WITH HOT AIR TO EXPOSE ASPHALT OR COATED WITH M-H MOD BIT FLASHING ADHESIVE PRIOR TO THE APPLICATION OF THE CAP SHEET FLASHING MATERIAL.

APPROVED COVERBOARD/OVERLAY OR APPROVED INSULATION  
INSULATION  
ROOF DECK

NOTE: FOR 20-YR SYSTEM, 2 PLYS OF SA BASE SHEET MUST BE INSTALLED. BASE SHEET MUST TURN UP VERTICAL SURFACE A MINIMUM OF 3".

**MULE-HIDE  
PRODUCTS CO., INC.  
2003**

**BASE FLASHING - AREA DIVIDER  
OPTION 3**

**SELF-ADHERING MOD BIT SYSTEMS**

**DETAIL NO.:  
MH-MB-AD3**